



Certificate of Accuracy of Translation

The undersigned,

Maki NAKAMURA

certifies:

- (1) I am fully conversant with both the English and the Japanese languages;
- (2) I have translated into English:
Japanese Patent Application SN 2001 - 025098
- (3) The translation is, to the best of my knowledge and belief, an accurate translation from the original into the English language.

Date: 20 / 11 / 2002
(Day / Month / Year)

Signature: Maki Nakamura

[DOCUMENT NAME] REQUEST FOR GRANT OF A PATENT

[REFERENCE NUMBER] 2038620049

[DATE OF FILING] February 1, 2001

[TO:] Commissioner of the Patent Office

[IPC] H04N 7/14

H04N 5/225

[INVENTOR]

[ADDRESS] c/o Matsushita Electric Industrial Co., Ltd., 1006,
Ooaza Kadoma, Kadoma-Shi, Osaka

[NAME] Kazuyuki IMAGAWA

[INVENTOR]

[ADDRESS] c/o Matsushita Electric Industrial Co., Ltd., 1006,
Ooaza Kadoma, Kadoma-Shi, Osaka

[NAME] Tetsuya YOSHIMURA

[INVENTOR]

[ADDRESS] c/o Matsushita Electric Industrial Co., Ltd., 1006,
Ooaza Kadoma, Kadoma-Shi, Osaka

[NAME] Katsuhiko IWASA

[APPLICANT]

[ID] 000005821

[NAME] Matsushita Electric Industrial Co., Ltd.

[AGENT]

[ID] 100097179

[PATENT ATTORNEY]

[NAME] Kazuyuki HIRANO

[INDICATION OF FEE]

[NUMBER OF PREPAID LEDGER] 058698

[FEE] 21000

[LIST OF ENCLOSURES]

[ITEM] Specification 1

[ITEM] Drawing 1

[ITEM] Abstract 1

[NUMBER OF GENERAL POWER OF ATTORNEY] 0013529

[PROOF] Required

[DOCUMENT NAME] SPECIFICATION

[TITLE OF THE INVENTION] IMAGE PROCESSING METHOD
AND APPARATUS

[CLAIMS]

[Claim1] An image processing method for evaluating matching between a template image and an input image by use of a similarity value map, the method including a step of generating an evaluation vector for each of the template image and the input image, wherein the evaluation vector includes a component in which an edge normal direction vector of a specified image undergoes even-numbered times angular transformation.

[Claim2] An image processing method comprising:

a step of inputting a specified image for both a template image and an input image and calculating an edge normal direction vector of the specified image;

a step of generating an evaluation vector from the edge normal direction vector;

a step of subjecting the evaluation vector to orthogonal

transformation;

a step of performing a product sum calculation of corresponding spectral data for each evaluation vector that has been subjected to orthogonal transformation and has been obtained for the template image and input image; and

a step of subjecting a result of the product sum calculation to inverse orthogonal transformation and generating a map of similarity values;

wherein a formula of the said similarity values, the said orthogonal transformation, and the said inverse orthogonal transformation each have linearity.

[Claim3] The image processing method of Claim 2, further comprising a step of compressing each evaluation vector that has been subjected to orthogonal transformation so as to reduce a processing amount.

[Claim4] The image processing method of Claim 2 to 3, wherein for the template image, the steps taken until the evaluation vector that has been subjected to orthogonal transformation is compressed are executed

before the input image is input, and its result is stored in a recording means.

[Claim5] The image processing method of Claim 2 to 4, wherein the evaluation vector is normalized with respect to a vector length.

[Claim6] The image processing method of Claim 2 to 5, wherein the evaluation vector of the template image is normalized by the number of edge normal direction vectors.

[Claim7] The image processing method of Claim 2 to 6, wherein a data amount is reduced by use of complex conjugate properties of orthogonal transformation before performing a product sum calculation, and the data amount is restored after performing the product sum calculation.

[Claim8] The image processing method of Claim 2 to 7, wherein the template image is enlarged/reduced to various sizes, and the evaluation vector of each size is subjected to addition processing.

[Claim9] The image processing method of Claim 8, wherein for the template image, the addition processing of the evaluation vector is carried out after executing the step of compressing each evaluation vector so as to

reduce the processing amount.

[Claim10] The image processing method of Claim 2 to 9, wherein the template image is an image of a typified face.

[Claim11] The image processing method of Claim 2 to 10, wherein a peak pattern that makes a peak of the similarity value steep is prepared, and a result obtained by subjecting data of this peak pattern to orthogonal transformation is applied to the product sum calculation.

[Claim12] The image processing method of Claim 2 to 10, wherein a mask pattern that depends on the template image is formed, and a result obtained by subjecting data of this mask pattern to orthogonal transformation is applied to the product sum calculation.

[Claim13] The image processing method of Claim 12, wherein the said mask pattern shows an average of a number of pixels in an image of the template image.

[Claim14] The image processing method of Claim 2 to 12, further comprising a step of, for the template image, processing positive and negative signs of the evaluation vector of the original template image and

generating an evaluation vector of a bilaterally symmetrical image with respect to the original template image, by which the generated evaluation vector is applied to the product sum calculation.

[Claim15] The image processing method of Claim 10, wherein a map of point biserial correlation coefficients is generated on the basis of an extracted face image, and a position of the face part is calculated.

[Claim16] The image processing method of Claim 10, wherein a distribution of projection values in a y-direction is calculated on the basis of the extracted face image by use of the mask pattern, and two maximum points are calculated from this distribution, and an range between these maximum points is output as a mouth range.

[Claim17] The image processing method of Claim 10, wherein the input image is divided into only the face image and parts other than the face image on the basis of the extracted face image, and a digital watermark is embedded only into the face image, and the face image into which the digital watermark has been embedded and parts other than the face image are combined together and are output.

[Claim18] The image processing method of Claim 10, wherein the input image is divided into only the face image and parts other than the face image on the basis of the extracted face image, and only the face image is edited, and the face image that has been edited and parts other than the face image are combined together and are output.

[Claim19] An image processing apparatus comprising:

a template image processing part for inputting a template image and calculating an edge normal direction vector of the template image, generating an evaluation vector from the edge normal direction vector, subjecting the evaluation vector to orthogonal transformation, and compressing the evaluation vector that has been subjected to the orthogonal transformation so as to reduce the processing amount;

an input image processing part for inputting an input image and calculating an edge normal direction vector of the input image, generating an evaluation vector from the edge normal direction vector, subjecting the evaluation vector to orthogonal transformation, and compressing the evaluation vector that has been subjected to the orthogonal transformation

so as to reduce the processing amount;

multiplication means for performing a product sum calculation of corresponding spectral data about each evaluation vector that has been subjected to the orthogonal transformation and has been obtained for the template image and the input image; and

inverse orthogonal transformation means for subjecting a result of the product sum calculation to inverse orthogonal transformation and generating a map of similarity values;

wherein the evaluation vector includes a component in which an edge normal direction vector of a specified image undergoes even-numbered times angular transformation, and a formula of the similarity values, the orthogonal transformation, and the inverse orthogonal transformation each have linearity.

[Claim20] The image processing apparatus of Claim 19, wherein the said template image processing part is provided with a recording means for recording the evaluation vector that has been compressed to reduce a processing amount and that has been subjected to orthogonal

transformation, and a result obtained by compressing the evaluation vector that has been subjected to orthogonal transformation is stored in the recording means before inputting the input image.

[Claim21] The image processing apparatus of Claim 19, further comprising: a conjugate compression means, provided between the said recording means and the said multiplication means, for reducing the data amount by use of complex conjugate properties of orthogonal transformation; and a conjugate restoring means, provided between the said multiplication means and the said inverse orthogonal transformation means, for restoring the data amount reduced by use of the complex conjugate properties of orthogonal transformation.

[Claim22] The image processing apparatus of Claim 19 to 21, further comprising: an enlargement/reduction means for enlarging/reducing the template image to various sizes; and an addition means for performing addition processing of the evaluation vector of each size.

[Claim23] The image processing apparatus of Claim 22, wherein the said addition means performs addition processing of the evaluation vector

of the template image after compressing the vector so as to reduce the processing amount.

[Claim24] The image processing apparatus of Claim 19, further comprising a peak pattern processing part for subjecting a peak pattern by which a peak of a similarity value is made steep to orthogonal transformation and compressing the peak pattern that has been subjected to the orthogonal transformation so as to reduce the processing amount, wherein a result obtained by subjecting data of this peak pattern to the orthogonal transformation is applied to a product sum calculation of the said multiplication means.

[Claim25] The image processing apparatus of Claim 19, further comprising a mask pattern processing part for forming a mask pattern that depends on the template image and generating data obtained by subjecting data of this mask pattern to orthogonal transformation and by compressing it, wherein a processing result of the said mask pattern processing part is applied to a product sum calculation of the said multiplication means.

[Claim26] The image processing apparatus of Claim 25, wherein the

said mask pattern shows a mean of the number of pixels inside an image of the template image.

[Claim27] The image processing apparatus of Claim 20, further comprising a symmetric vector generation means for processing positive and negative signs of the evaluation vector of an original template image recorded in the said recording means, and generating an evaluation vector of a bilaterally symmetric image with respect to the original template image, wherein the evaluation vector generated by the symmetric vector generation means is applied to a product sum calculation of the said multiplication means.

[Claim28] The image processing apparatus of Claim 19, further comprising a η map forming means for forming a map of a point biserial correlation coefficient on the basis of an extracted face image, and an extraction means for calculating a position of a face part from the formed map.

[Claim29] The image processing apparatus of Claim 19, further comprising a maximum point extraction means for calculating a projection

value distribution in a y direction by use of a mask pattern on the basis of an extracted face image, and calculating two maximum points from this distribution, and outputting a range between the maximum points such as a mouth range.

[Claim30] The image processing apparatus of Claim 19, further comprising: a face image cutting-out means for separating an input image into only a face image and parts excluding the face image on the basis of an extracted face image; a digital watermark embedding means for embedding a digital watermark only into the face image; and an image synthesizing means for combining the face image into which the digital watermark has been embedded with parts excluding the face image and outputting them.

[Claim31] The image processing apparatus of Claim 19, comprising a face image cutting-out means for separating an input image into only a face image and parts excluding the face image on the basis of an extracted face image; an image edge correction means for editing only the face image; and an image synthesizing means for combining an edited face

image with parts excluding the face image and outputting them.

[DETAILED DESCRIPTION]

【 0 0 0 1 】

[TECHNICAL FIELD]

The present invention relates to an image processing method for detecting an object from an input image by use of a template image, and relates to an image processing apparatus therefor.

【 0 0 0 2 】

[PRIOR ART]

Conventionally, a technique is well known in which a template image is pre-registered, and the position in an input image of an image similar to the template image is detected by pattern matching between the input image and the template image.

【 0 0 0 3 】

However, since distorted perceptions are liable to be shaped according to how the background of the image similar to the template image is formed, Japanese Published Unexamined Patent Application No.

Hei-5-28273 discloses a technique that has been developed to solve this problem.

【 0 0 0 4 】

In this publication, a similarity value between the template image and the image corresponding to the template image is defined by the following mathematical formula.

【Formula 1】

Cv: Correlation coefficient (similarity value)

M: Number of pixels of template image in x direction

N: Number of pixels of template image in y direction

Sx: Derivative value of input image S in x direction

Sy: Derivative value of input image S in y direction

Tx: Derivative value of template image T in x direction

Ty: Derivative value of template image T in y direction

In detail, an inner product ($\cos\theta$) of an angle θ between a normal direction vector of the edge of the template image and a normal direction vector of the edge of the input image is a component of the similarity

value.

【 0 0 0 5 】

[TECHNICAL PROBLEM]

However, there is a problem in that, as described later in detail, if the brightness of a background periphery of an image of an object is uneven, the positive and negative of the inner product are reversed, so that the similarity value becomes unsuitable for the real image, and distorted perceptions are easily produced, thus making it difficult to obtain a desirable recognition result.

【 0 0 0 6 】

Additionally, the similarity value formula is nonlinear with respect to the normal direction vectors of the edges of the input and template images, and processing for the template image and processing for the input image must be performed simultaneously.

【 0 0 0 7 】

Further, the template image is scanned on the input image, and a correlated calculation of the input image and the reference image must be

performed for each scanning point, and therefore, in practicality, a resulting expanding calculation amount makes real-time processing impossible.

【 0 0 0 8 】

It is therefore an object of the present invention to provide an image processing method and an image processing apparatus capable of obtaining an accurate, clear recognition result and capable of performing high speed processing.

【 0 0 0 9 】

[MEANS]

In an image processing method according to a first aspect of the present invention, matching between a template image and an input image is evaluated by use of a similarity value map, and an evaluation vector is generated for each of the template and input images, and the evaluation vector includes a component in which a normal direction vector of an edge of a specified image undergoes even-numbered times angular transformation.

【 0 0 1 0 】

With this structure, an image processing method capable of obtaining a clear, accurate recognition result and capable of performing high speed processing can be realized.

【 0 0 1 1 】

[EMBODIMENTS OF THE INVENTION]

In an image processing method according to a first aspect of the present invention, matching between a template image and an input image is evaluated by use of a similarity value map, and an evaluation vector is generated for each of the template and input images, and the evaluation vector includes a component in which a normal direction vector of an edge of a specified image undergoes even-numbered times angular transformation.

【 0 0 1 2 】

With this structure, the matching therebetween can be properly evaluated with no influence on the similarity value even in a case in which the positive and negative of an inner product ($\cos\theta$) of an angle θ between

a normal direction vector of the edge of the template image and a normal direction vector of the edge of the input image are reversed because of unevenness in brightness of its background.

【 0 0 1 3 】

An image processing method according to a second aspect of the present invention includes a step of inputting a specified image for each of a template image and an input image and calculating a normal direction vector of an edge of the specified image; a step of generating an evaluation vector from the edge normal direction vector; a step of subjecting the evaluation vector to an orthogonal transformation; a step of performing a product sum calculation of corresponding spectral data for each evaluation vector, which has been subjected to orthogonal transformation, obtained for the template image and input image; and a step of subjecting a result of the product sum calculation to an inverse orthogonal transformation and generating a map of similarity values; in which a formula of the similarity values, the orthogonal transformation, and the inverse orthogonal transformation each have linearity.

【 0 0 1 4 】

With this structure, a Fourier transformation value of the template image and a Fourier transformation value of the input image do not need to be simultaneously calculated. In other words, the Fourier transformation value of the template image can be obtained prior to that of the input image, thus making it possible to lighten the processing burden and improve processing speed.

【 0 0 1 5 】

An image processing method according to a third aspect of the present invention includes a step of compressing each evaluation vector, which has been subjected to the orthogonal transformation, so as to reduce the processing amount.

【 0 0 1 6 】

With this structure, what is processed is limited only to an effective component (e.g., low-frequency component), and processing speed can be improved.

【 0 0 1 7 】

In an image processing method according to a fourth aspect of the present invention, for the template image, the steps taken until the evaluation vector that has been subjected to the orthogonal transformation is compressed are executed before the input image is input, and its result is stored in a recording unit.

【 0 0 1 8 】

With this structure, the processing relating to the template image is completed merely by reading from the recording unit, and processing speed can be improved.

【 0 0 1 9 】

In an image processing method according to a fifth aspect of the present invention, the evaluation vector is normalized with respect to a vector length.

【 0 0 2 0 】

With this structure, the stability of pattern extraction can be improved without undergoing length variations though the strength of the edge of the input image varies, and the vector length varies according to a

photographic condition.

【 0 0 2 1 】

In an image processing method according to a sixth aspect of the present invention, the evaluation vector of the template image is normalized by the number of edge normal direction vectors.

【 0 0 2 2 】

Therefore, independent of whether the number of edges of the template image is large or small, a similarity can be evaluated on the same scale by dividing it by n and normalizing it.

【 0 0 2 3 】

In an image processing method according to a seventh aspect of the present invention, a data amount is reduced by use of complex conjugate properties of an orthogonal transformation before performing a product sum calculation, and the data amount is restored after performing the product sum calculation.

【 0 0 2 4 】

With this structure, the data amount can be greatly reduced to

improve processing speed, and memory capacity can be saved.

【 0 0 2 5 】

In an image processing method according to an eighth aspect of the present invention, the template image is enlarged/reduced to various sizes, and the evaluation vector of each size is subjected to addition processing.

【 0 0 2 6 】

With this structure, matching does not need to be repeatedly carried out for each size, and processing speed can be improved.

【 0 0 2 7 】

In an image processing method according to a ninth aspect of the present invention, for the template image, the addition processing of the evaluation vector is carried out after executing the step of compressing each evaluation vector so as to reduce the processing amount.

【 0 0 2 8 】

With this structure, what is subjected to addition processing can be reduced, and processing speed can be improved.

【 0 0 2 9 】

In an image processing method according to a tenth aspect of the present invention, the template image is an image of a typified face.

【 0 0 3 0 】

With this structure, not only the total position of a face but also the partial position of a main face part, such as the eyes, nose, or mouth, can be recognized.

【 0 0 3 1 】

In an image processing method according to an 11th aspect of the present invention, a peak pattern that makes a peak of the similarity value steep is prepared, and a result obtained by subjecting data of this peak pattern to an orthogonal transformation is applied to the product sum calculation.

【 0 0 3 2 】

With this structure, a part similar to a template can be detected from the input image more clearly and stably while reflecting the peak pattern.

【 0 0 3 3 】

In an image processing method according to a 12th aspect of the present invention, a mask pattern that depends on the template image is formed, and a result obtained by subjecting data of this mask pattern to an orthogonal transformation is applied to the product sum calculation.

【 0 0 3 4 】

With this structure, closer detection can be performed while adding attributes other than the shape of the template image.

【 0 0 3 5 】

In an image processing method according to a 13th aspect of the present invention, the mask pattern shows an average of a number of pixels in an image of the template image.

【 0 0 3 6 】

With this structure, attributes of the template image can be reflected by a simple mask pattern.

【 0 0 3 7 】

An image processing method according to a 14th aspect of the present invention further includes a step of, for the template image,

processing positive and negative signs of the evaluation vector of the original template image and generating an evaluation vector of a bilaterally symmetrical image with respect to the original template image, by which the generated evaluation vector is applied to the product sum calculation.

【 0 0 3 8 】

With this structure, the recording amount of the template image can be saved, and the evaluation vector of the template image that has been bilaterally reversed can be generated without direct calculation, thus making it possible to improve processing speed.

【 0 0 3 9 】

In an image processing method according to a 15th aspect of the present invention, a map of point biserial correlation coefficients is generated on the basis of an extracted face image, and a position of the face part is calculated.

【 0 0 4 0 】

With this structure, the position of the face part can be specified

more accurately.

【 0 0 4 1 】

In an image processing method according to a 16th aspect of the present invention, a distribution of projection values in a y-direction is calculated on the basis of the extracted face image by use of the mask pattern, and two maximum points are calculated from this distribution, and an extent between these maximum points is output as a mouth range.

【 0 0 4 2 】

With this structure, the mouth range can be specified more accurately.

【 0 0 4 3 】

In an image processing method according to a 17th aspect of the present invention, the input image is divided into only the face image and parts other than the face image on the basis of the extracted face image, and a digital watermark is embedded only into the face image, and the face image into which the digital watermark has been embedded and parts other than the face image are combined and output.

【 0 0 4 4 】

With this structure, watermark data can be concentratively embedded into the face part that is liable to be falsified.

【 0 0 4 5 】

In an image processing method according to an 18th aspect of the present invention, the input image is divided into only the face image and parts other than the face image on the basis of the extracted face image, and only the face image is edited, and the face image that has been edited and parts other than the face image are combined and output.

【 0 0 4 6 】

With this structure, only the face image can be corrected without exerting an influence on parts other than the face.

【 0 0 4 7 】

(Embodiment 1)

Referring to Fig. 1 through Fig. 8, the basic form of an image processing apparatus of the present invention will be described.

【 0 0 4 8 】

As shown in Fig. 1, the image processing apparatus according to Embodiment 1 includes two different processing parts, i.e., a template image processing part 100 and an input image processing part 200, and evaluates matching between a template image and an input image by use of a map of similarity values L. In this image processing apparatus, both the template image processing part 100 and the input image processing part 200 perform orthogonal transformation with linearity, then perform multiplication, and calculate the similarity values L by inverse orthogonal transformation.

【 0 0 4 9 】

It should be noted that FFT (Fast Discrete Fourier Transformation) is used as an orthogonal transformation in all embodiments described later. However, not only FFT but also Hartley transformation or number theoretic transformation can be used, and "Fourier transformation" in the following description can be replaced by Hartley transformation or number theoretic transformation.

【 0 0 5 0 】

Further, both the template image processing part 100 and the input image processing part 200 employ an inner product of edge normal direction vectors so that a correlation becomes proportionately higher with proximity between the directions of the edge normal direction vectors. This inner product is evaluated by use of an even-numbered times angle expression. For convenience, only a double size angle will be hereinafter described as an example of even-numbered times angle, but the same effect with the present invention can be produced in other even-numbered times angles such as a quadruple size or a sextuple size.

【 0 0 5 1 】

Next, the template image processing part 100 will be described. An edge extraction unit 1 applies differential processing (edge extraction) to a template image in x and y directions, and outputs an edge normal direction vector of the template image.

【 0 0 5 2 】

In this embodiment, a Sobel filter of 【Formula 2】 is used for the x direction, and a Sobel filter of 【Formula 3】 is used for the y direction.

【 0 0 5 3 】

An edge normal direction vector of the template image defined by the following formula is obtained with these filters.

【Formula 4】

This embodiment takes an example in which an image of a person in a specific posture who is walking through a pedestrian crossing is extracted from an input image of the vicinity of the pedestrian crossing.

【 0 0 5 4 】

The template image of the person is that of Fig. 2(a), for example. If the filter processing of Formula 2 is applied to the template image of Fig. 2(a), a result (x component) as shown in Fig. 2(b) will be obtained, and, if the filter processing of Formula 3 is applied to the template image of Fig. 2(a), a result (y component) as shown in Fig. 2(c) will be obtained.

【 0 0 5 5 】

An evaluation vector generation unit 2 inputs an edge normal direction vector of the template image from the edge extraction unit 1, and outputs the evaluation vector of the template image to an orthogonal

transformation unit 3 through processings described later.

【 0 0 5 6 】

First, the evaluation vector generation unit 2 normalizes the length of the edge normal direction vector of the template image according to the following formula.

【Formula 5】

Generally, the edge strength of the input image varies according to a photographic condition. However, an angular difference between the edges of the input and template images (or, a subordinate function value that varies according to this angular difference) is unsusceptible to the photographic condition.

【 0 0 5 7 】

Therefore, in the present invention, the edge normal direction vector of the input image is normalized to be 1 in length in the input image processing part 200, as described later. According to this, the edge normal direction vector of the template image is normalized to be 1 in length in the template image processing part 100.

【 0 0 5 8 】

As a result, the stability of pattern extraction can be improved. Usually, it is desirable to have a normalization length of 「1」 , but other constants can be used.

【 0 0 5 9 】

Concerning a trigonometric function, the following double size formula is established as is well known.

【Formula 6】

The evaluation vector generation unit 2 calculates the evaluation vector of the template image defined by the following formula.

【Formula 7】

When assumed to be a threshold (for fine edge removal), the evaluation vector V of the template image is:

if

else

wherein n is the number of > a.

Formula 7 will be described. The reason why a vector smaller

than constant "a" is set as a 0 vector is to remove a noise, for example.

【 0 0 6 0 】

Next, a description will be given of the fact that x and y components of this evaluation vector are each divided by "n" for normalization.

【 0 0 6 1 】

Generally, the shape of the template image is arbitrary, and the shape of the edge is various. For example, there is a situation in which the number of edges is small as shown in Fig. 8(a), or the number of edges is larger (than that of Fig. 8(a)) as shown in Fig. 8(b). Therefore, in this embodiment, the similarity is intended to be evaluated on the same scale by dividing it by "n" for normalization independent of whether the number of the edges is small or large.

【 0 0 6 2 】

However, the normalizing processing of dividing it by "n" does not necessarily need to be performed, and normalizing processing can be omitted in a situation in which only one template image is used or in

which only template images the same as the number of edges are used.

【 0 0 6 3 】

Next, a description will be given of the fact that the x and y components of Formula 7 serve as a subordination function of the cosine/sine for a double size of the x and y components of Formula 5.

【 0 0 6 4 】

If the inner product $\cos\theta$ of an angle θ between an evaluation vector T of the template image and an evaluation vector I of the input image is used as a similarity scale as in the conventional technique, the following problem will arise.

【 0 0 6 5 】

For example, let us suppose that the template image is that of Fig. 7(a), and the input image is that of Fig. 7(b). In the background of Fig. 7(b), the left background part of an image of a specified object is brighter than the image of the specified object, and the right background part of the image of the specified object is darker than the image of the specified object.

【 0 0 6 6 】

If considered only from the images, the images of the specified object completely coincide with each other when the center of the template image of Fig. 7(a) coincide with the center of the input image of Fig. 7(b), and therefore the similarity value must be the maximum at this time. Herein, if the edge normal direction vector that is directed outward from the image of the object is positive, the edge normal direction vector must be directed in the same direction (outward/inward) in the brighter background part of Fig. 7(b) and in the darker background part thereof when deriving from the image of the specified object.

【 0 0 6 7 】

However, if the brightness of the background of Fig. 7(b) is uneven in the right and left background parts with the specified object therebetween at this time, the directions are opposed as shown by arrows in Fig. 7(b) (i.e., outward from the specified object in the brighter background part, and inward from the specified object in the darker background part).

【 0 0 6 8 】

Originally, it is to reach the maximum similarity value, but the similarity value does not necessarily become high in this case, and thereby a distorted perception is easily shaped.

【 0 0 6 9 】

A detailed description of the above problem will be given with reference to Fig. 6. In the case an angle between the evaluation vector T of the template image and the evaluation vector I of the input image is represented as θ , and its inner product, i.e., $\cos\theta$ is used as a similarity value, the direction of the evaluation vector I of the input image has two possibilities, i.e., I of Fig. 6 and I' precisely opposite thereto because of unevenness in brightness of the background that exists in the periphery of the image of the specified object, as described above.

【 0 0 7 0 】

Therefore, the inner product used as a similarity scale will have two products, i.e., $\cos\theta$ and $\cos\theta'$.

【 0 0 7 1 】

Herein, $\theta + \theta' = \pi$, and $\cos\theta' = \cos(\pi - \theta) = -\cos\theta$.

【 0 0 7 2 】

Therefore, if $\cos\theta$ is used as the similarity scale, a similarity value will be oppositely reduced when there is a need to act properly to increase the similarity value, and the similarity value will be oppositely increased when there is a need to act properly to reduce the similarity value.

【 0 0 7 3 】

In other words, according to the prior art similarity value, matching between the template image and the input image cannot be correctly evaluated. As a result, disadvantageously, a wrong recognition is easily formed by the conventional technique, and a recognition result will not be clear even if images are shaped.

【 0 0 7 4 】

Therefore, in the present invention, a cosine that is a double size of θ , i.e., $\cos(2\theta)$ is used for the formula of the similarity value. Thereby, $\cos(2\theta') = \cos(2\theta)$ from the double size formula of Formula 6 even if $\cos\theta' = -\cos\theta$. In other words, the similarity value rises irrespective of the

background when there is a need to act to increase the similarity value. Therefore, the matching therebetween can be correctly evaluated in spite of the unevenness in brightness of the background. This applies to the quadruple size or the sextuple size as well as the double size.

【 0 0 7 5 】

Moreover, the properties of the similarity value monotonously decreasing with respect to angle θ do not change even if an even-numbered times angle cosine is used.

【 0 0 7 6 】

Therefore, according to the present invention, patterns can be stably extracted by an even-numbered times angle evaluation regardless of the brightness condition of the background.

【 0 0 7 7 】

More specifically, the similarity value is defined by the following formula in the present invention.

【Formula 8】

Similarity value

:Evaluation vector of input image

:Evaluation vector of template image

Since Formula 8 consists only of addition and multiplication, the similarity value is linear for each evaluation vector of the input and template images. Therefore, when Formula 8 is subjected to Fourier transformation, Formula 9 is obtained by a discrete correlation theorem of Fourier transformation (reference: Fast Fourier Transformation translated by Hiroshi Miyakawa published by Science and Technology).

【Formula 9】

Fourier transformation values of K_x, K_y

Fourier transformation complex conjugate of V_x, V_y

Hereinafter, Fourier transformation value represented as \sim , and complex conjugate represented as $*$.

- 【 0 0 7 8 】

The similarity value of Formula 8 is obtained by subjecting Formula 9 to inverse Fourier transformation. From careful consideration of Formula 9, the following two respects will become apparent.

【 0 0 7 9 】

First, (1) the Fourier transformation value of the template image and the Fourier transformation value of the input image can be simply multiplied together in a transformation value that has been subjected to orthogonal transformation.

【 0 0 8 0 】

Secondly, (2) the Fourier transformation value of the template image and the Fourier transformation value of the input image do not need to be simultaneously calculated, and the Fourier transformation value of the template image may be calculated prior to that of the input image.

【 0 0 8 1 】

Therefore, in this embodiment, the template image processing part 100 is provided with a recording unit 5 to record the output of a compression unit 4 before inputting the input image. Thereby, after the input image is input to the input image processing part 200, the template image processing part 100 has no need to process the template image, and the processing performance can be concentrated on processing subsequent

to the input image processing part 200 and a multiplication unit 10, thus making it possible to improve the processing speed.

【 0 0 8 2 】

Next, a description will be given of a structure subsequent to the evaluation vector generation unit 2. As shown in Fig. 1, in the template image processing part 100, the evaluation vector of the template image that is output from the evaluation vector generation unit 2 is subjected to Fourier transformation by the orthogonal transformation unit 3, and is output to the compression unit 4.

【 0 0 8 3 】

The compression unit 4 reduced the evaluation vector that has been subjected to Fourier transformation, and stores it in the recording unit 5. As shown in Fig. 3, the evaluation vector subjected thereto includes various frequency components in both x and y directions. By experiments carried out by the present inventors, it is known that sufficient accuracy can be obtained by processing the low frequency components (e.g., halves on the low frequency side in the x and y directions,

respectively) without processing all of the frequency components. In Fig. 3, the range $(-a \leq x \leq a, -b \leq y \leq b)$ having no oblique line is an original one, and the range $(-a/2 \leq x \leq a/2, -b/2 \leq y \leq b/2)$ having oblique lines is the one that has been reduced. That is, the processing amount becomes 1/4 times as much as before.

【 0 0 8 4 】

Thereby, an object to be processed can be reduced, and the processing speed can be improved.

【 0 0 8 5 】

The compression unit 4 and the recording unit 5 can be omitted when a data amount is small, or high-speed processing is not required.

【 0 0 8 6 】

Next, the input image processing part 200 will be described. The input image processing part 200 performs almost the same processing as the template image processing part 100. That is, according to Formula 2 and Formula 3, the edge extraction unit 6 outputs an edge normal direction vector of the input image defined by the following formula.

【Formula 10】

Edge normal direction vector of input image)

I_x: Derivative value of input image in x direction

I_y: Derivative value of input image in y direction

The evaluation vector generation unit 7 inputs the edge normal direction vector of the input image from the edge extraction unit 6, and outputs an evaluation vector of the input image defined by the following two formulas.

【Formula 11】

Length normalized vector of input image)

【Formula 12】

When assumed to be a threshold (for fine edge removal), the evaluation vector K of the input image is:

if

else

The input image processing part 200 differs from the template image processing part 100 only in the fact that normalizing processing of

the division by "n" is not performed. In other words, evaluation by the even-numbered times angle, the normalizing processing to 1 in length, and the noise removal processing are performed in the same way as in the template image processing part 100.

【 0 0 8 7 】

Next, a structure subsequent to the evaluation vector generation unit 7 will be described. As shown in Fig. 1, in the input image processing part 200, the evaluation vector of the input image that is output from the evaluation vector generation unit 7 is subjected to Fourier transformation by the orthogonal transformation unit 8, and is output to the compression unit 9.

【 0 0 8 8 】

The compression unit 9 reduces the evaluation vector that has been subjected to Fourier transformation, and outputs it to the multiplication unit 10. Herein, the compression unit 9 reduces the object to be processed to the same frequency band as the compression unit 4 (e.g., halves on the low frequency side in the x and y directions, respectively, in

this embodiment).

【 0 0 8 9 】

The compression unit 9 can be, of course, omitted when the data amount is small, or when high-speed processing is not required, and the compression unit 9 is likewise omitted when the compression unit 4 is omitted in the template image processing part 100.

【 0 0 9 0 】

Next, the multiplication unit 10 and other construction subsequent to this will be described. When the processing in the template image processing part 100 and in the input image processing part 200 is completed, the multiplication unit 10 inputs a Fourier transformation value of each evaluation vector of the template and inputs images from the recording unit 5 and the compression unit 9.

【 0 0 9 1 】

Thereafter, the recording unit 5 performs a product-sum-calculation according to Formula 9, and outputs the result (i.e., Fourier transformation value of the similarity value L) to an inverse orthogonal transformation

unit 11.

【 0 0 9 2 】

The inverse orthogonal transformation unit 11 subjects the Fourier transformation value of the similarity value L to inverse Fourier transformation, and outputs the map $L(x,y)$ of the similarity value L to a map processing unit 12. The map processing unit 12 extracts a high-value point (peak) from the map $L(x,y)$, and outputs its position and its value. The map processing unit 12 and the construction subsequent to this can be freely arranged if necessary.

【 0 0 9 3 】

Next, a processing example by the template image of Fig. 2 will be described with reference to Fig. 4 and Fig. 5. If the input image is as shown in Fig. 4(a), the edge extraction unit 6 extracts an edge component in the x direction as shown in Fig. 4(b), and extracts an edge component in the y direction as shown in Fig. 4(c).

【 0 0 9 4 】

As a result of the aforementioned processing, a similarity value

map $L(x,y)$ shown in Fig. 5(a) is obtained. Herein, the front end of the arrow indicated as the "maximum value" is a peak of this map, and, as is apparent from a comparison with the input image of Fig. 5(b), it is understood that the correct point can be clearly recognized by only one point.

【 0 0 9 5 】

In the conventional technique, the calculation must be performed by the number of times of the product, i.e., $2AB$ in order to successively scan the template image on input images and to obtain ρ_{xy} of Formula 1 at each position, wherein the size of the input image is $A(=2\gamma)$ and the size of the template image is B . Herein, the number of calculations is evaluated by the number of times of the product with high calculation costs.

【 0 0 9 6 】

In contrast, in this embodiment, FFT is performed twice by the orthogonal transformation unit 3 and 8, the product sum calculation is then performed by the multiplication unit 10, and inverse FFT is performed once by the inverse orthogonal transformation unit 11. The number of

calculations is merely the number of times of the product of $3\{(2\gamma-4)A+4\}+2A$.

【 0 0 9 7 】

In a comparison of the number of calculations therebetween, the number of calculations of the product according to this embodiment becomes about 1/100 of the number of calculations of the product according to the conventional technique, if $A=256\times 256=2^{16}$, and $B=60\times 60$. As a result, unusually high-speed processing can be carried out.

【 0 0 9 8 】

The discrete correlation theorem of Fourier transformation cannot be used in such a nonlinear formula as Formula 1 of the conventional technique.

【 0 0 9 9 】

Therefore, in the conventional technique, processing for the template image cannot be performed prior to that for the input image as shown in Fig. 1 of this embodiment. In other words, in the conventional technique, both the template image and the input image must be

simultaneously processed. Also in this respect, the processing speed in this embodiment becomes higher than that in the conventional technique.

【 0 1 0 0 】

(Embodiment 2)

In this embodiment, a conjugate compression unit 13 and a conjugate restoring unit 14 are added to the elements of Fig. 1 as shown in Fig. 9. The conjugate compression unit 13 further halves the Fourier transformation value of the evaluation vector of the template image that has been read from the recording unit 5 by use of complex conjugate properties of Fourier transformation.

【 0 1 0 1 】

This respect will be described. The following formula is established for the spectrum obtained by real number Fourier transformation.

【Formula 13】

In detail, a spectral value at a specific point is equal to the complex conjugate of a spectral value at a position symmetrical to that point in a uv

coordinate system. Use of this property makes it possible to reduce the processing amount by half of the uv coordinate system as shown in Fig. 10(a).

【 0 1 0 2 】

Since the compression unit 4 and the compression unit 9 further compress it, the data amount can be reduced to 1/8 of the original data as shown in Fig. 10(b). Therefore, the processing speed can be improved, and memory capacity can be saved.

【 0 1 0 3 】

As a result, in this embodiment, the Fourier transformation value that the conjugate compression unit 13 has read from the recording unit 5 is halved, and is output to the multiplication unit 10. Thereafter, the conjugate reconstruction unit 14 performs processing by which the output from the multiplication unit 10 is doubled, and outputs it to the inverse orthogonal transformation unit 11.

【 0 1 0 4 】

These constitute the basis of the present invention. A useful

technique will be hereinafter disclosed by application of this basis.

【 0 1 0 5 】

(Embodiment 3)

In this embodiment, a first example and a second example will be described. A technique for performing face extraction by using an enlarged/reduced template image is disclosed in either example. According to this technique, processing by use of similar templates different in size can be carried out efficiently and at high speed. The application of this technique is not limited only to face extraction.

【 0 1 0 6 】

「First Example」

Fig. 11(a) is a block diagram of a template image processing part according to Embodiment 3 (first example) of the present invention. Some modifications have been made to the template image processing part 100 of Fig. 1 or Fig. 9 as shown in the figure.

【 0 1 0 7 】

First, when a template image is input to a template image

processing part 101, the image is enlarged/reduced by a enlargement/reduction unit 15. Thereafter, the enlarged/reduced template image is output to an edge extraction unit 1.

【 0 1 0 8 】

When an evaluation vector generation unit 2 outputs the evaluation vector of the template image, an addition unit 16 applies addition processing to this, and data obtained by the addition processing is output to an orthogonal transformation unit 3.

【 0 1 0 9 】

The addition unit 16 performs addition processing for each size range according to the following formula.

【Formula 14】

Evaluation vector of template image

wherein the size range is $a \sim b$.

Although image processing is carried out by use of one template image in Embodiments 1 and 2, templates with multiple sizes are processed by use of a plurality of templates in this embodiment.

【 0 1 1 0 】

Moreover, the sizes of the templates are each separated into a specific range, and a template processing result is superimposed thereon.

【 0 1 1 1 】

Fig. 12 shows an example of an input image that includes a face image of a person. In this example, a template image of a straight face, such as that of Fig. 13(a), is prepared. A template image of a face inclined at a specific angle as shown in Fig. 13(d) is further prepared. The degree to which the face to be prepared is inclined can be appropriately selected.

【 0 1 1 2 】

When the edges of the template images of Figs. 13(a) and 13(d) are extracted, appearances shown in Fig. 13(b) and 13(e), respectively, are obtained in this embodiment. Further, when the image of Fig. 13(a) or 13(d) is input, an evaluation vector corresponding to the edge image is generated as shown in Fig. 13(c) or 13(f).

【 0 1 1 3 】

As in Embodiments 1 and 2, data concerning the template images are stored in the recording unit 5.

【 0 1 1 4 】

When the input image is input, a procedure subsequent to those of the input image processing part 200 and the multiplication unit 10 is performed in the same way as in Embodiments 1 and 2.

【 0 1 1 5 】

Corresponding similarity value maps are calculated for superimposed template data of all size ranges of the template images.

【 0 1 1 6 】

Thereby, a detection result, such as that shown in Fig. 14, is obtained. As is apparent from Fig. 14, not only the overall position of the face but also its size and the positions of the main face parts, such as the eyes, nose, and mouth, can be recognized.

【 0 1 1 7 】

At this time, it is desirable to display the processing result on a display or to output it to a printer as shown in Fig. 14 in the stage

subsequent to the map processing unit 12.

【 0 1 1 8 】

According to First Example, the following effects can be obtained.

(1) Even if template data in a specific size range is added, and image processing is performed with layered templates, a part similar to the template often shows a high similarity value. Therefore, when similarity values of all sizes are calculated, the processing of the product sum calculation part and the processing of the inverse orthogonal transformation part must be repeatedly performed NM times, wherein N is the number of the templates, and M is the number of all sizes. On the other hand, the number of processings reaches NM/H by use of the superimposed template, wherein H is the width of a superimposed range. Therefore, improvements in efficiency can be accomplished, and image processing can be carried out at a higher speed for face extraction, for example.

【 0 1 1 9 】

(2) Additionally, a rough candidate range of eyes, nose, and mouth

can be extracted not only merely by outputting the positional data for a face but also by superimposing the template on the face candidate position as shown in Fig. 14.

【 0 1 2 0 】

The positions of face parts, such the eyes, nose, and mouth, can also be more accurately extracted by processing the images in these ranges much more finely, as described in the following embodiments.

【 0 1 2 1 】

「Second Example」

In this example, a template image processing part 102 is constructed as shown in Fig. 11(b). That is, the position of the addition unit 16 is moved between the compression unit 4 and the recording unit 5, in comparison with the First Example. Thereby, the addition unit 16 is formed to perform addition processing according to the following formula.

【Formula 15】

wherein the size range is $a \sim b$.

The similarity value formula that is linear before being subjected to

Fourier transformation is still linear after being subjected thereto. Therefore, the position of the addition unit 16 can be changed from the First Example to the Second Example, for example.

【 0 1 2 2 】

Thereby, an object to be processed by the addition unit 16 can be reduced more than in the First Example because the object is compressed by compression unit 4. Therefore, suitably, processing speed can be improved.

【 0 1 2 3 】

(Embodiment 4)

Embodiment 4 will be described with reference to Fig. 15 and Fig. 16. This Embodiment discloses an efficient technique for turning the value of the maximum point of the similarity value map described in embodiments 1 and 2 into a stronger peak value.

【 0 1 2 4 】

Generally, in the similarity value map, a peak appears in a part overlapping with the template image. In this embodiment, a peak pattern

"p" around and including a maximum point is used as a filter for the similarity value map, and the value of a part similar to the peak pattern in the similarity value map is amplified.

【 0 1 2 5 】

As shown in Fig. 15, in this embodiment, a peak pattern processing part 300 is added to the structure of Fig. 1 showing embodiment 1.

【 0 1 2 6 】

Fig. 16 shows a mask for this peak pattern. As indicated in Fig. 16, in this peak pattern, normalization is made to set an average value at 0.

【 0 1 2 7 】

In the peak pattern processing part 300, an orthogonal transformation unit 17 subjects this peak pattern to Fourier transformation, and a compression unit 18 compresses a Fourier transformation value so as to record compressed data in a recording unit 19.

【 0 1 2 8 】

Since the mask is used, the similarity value formula is established not by Formula 8 but by the following formula that reflects the mask.

【Formula 16】

Peak pattern low frequency spectrum

$L(u,v)$: Similarity value before filtering

$M(u,v)$: Similarity value after filtering

Therefore, the multiplication unit 10 reads data from the recording unit 5, the recording unit 19, and the compression unit 9, then performs a product-sum-calculation, and outputs the Fourier transformation value of the similarity value corrected by the peak pattern.

【 0 1 2 9 】

A peak pattern filter can filter the similarity value map L according to the following formula; but, if so, a large amount of product sum calculations will be inefficiently needed.

【Formula 17】

In contrast, in this embodiment, simple, accurate processing is performed according to Formula 16 without performing a large amount of calculations like Formula 17.

【 0 1 3 0 】

Therefore, according to this embodiment, the peak point of the similarity value map can be efficiently amplified. Additionally, a part similar to the template can be clearly and stably detected from the input image while reflecting the peak pattern.

【 0 1 3 1 】

(Embodiment 5)

In this embodiment, a pixel mean in the range of the template image as well as the similarity value between the edge of the input image and the edge of the template image is added to a similarity judgment.

【 0 1 3 2 】

This structure is shown in Fig. 17. Like Fig. 15, a mask pattern processing part 400 is added to the structure of Fig. 1 of Embodiment 1.

【 0 1 3 3 】

However, the structure of Fig. 17 differs from that of Fig. 15 in the fact that the mask pattern processing part 400 is used not to input a peak pattern but to input a template image, and that a mask pattern generation unit 20 is provided for generating a mask pattern that depends on this

image.

【 0 1 3 4 】

Like Fig. 15, the output of the mask pattern generation unit 20 is subjected to Fourier transformation by the orthogonal transformation unit 21, is then compressed by the compression unit 22, and is recorded in the recording unit 23.

【 0 1 3 5 】

Further, since a mask is used, the similarity value formula is expressed not as Formula 8 but as the following formula that reflects the mask.

【Formula 18】

$Q(x,y)$: Pixel-average-added similarity value

$q(l,m)$: Mask pattern

$L(x,y)$: Similarity value before filtering

$I(x,y)$: Input image data

For the same reason mentioned in Embodiment 4, a large amount of product sum calculations will be inefficiently needed if multiplication is

performed in this way.

【 0 1 3 6 】

Formula 19 is obtained by subjecting this to Fourier transformation, and the calculation can be performed very simply.

【Formula 19】

【 0 1 3 7 】

Therefore, the multiplication unit 10 performs a product-sum-calculation according to Formula 19.

【 0 1 3 8 】

Next, the relationship between the template image and the mask pattern will be described with reference to Fig. 18. Herein, in order to add a pixel mean in the range of the template image to a similarity judgment, the mask pattern generation unit 20 generates a mask pattern as shown in Fig. 18(b) for a template image as shown in Fig. 18(a)

【 0 1 3 9 】

In greater detail, in the template image of Fig. 18(a), a value of $1/N$ is set at each point of the inner part (inside the circle) whose pixel mean is

to be calculated, and a value of 0 is set at other points. Herein, N is the number of points in the inner part, and a result of an addition of the value of all points of the mask pattern is 1.

【 0 1 4 0 】

According to this embodiment, a mean of pixel values inside the image can also be added to the similarity value, and a specified object can be extracted from the input image more accurately and more efficiently.

【 0 1 4 1 】

A mean of a square value of each pixel can be calculated such that data in which each pixel of the input image is squared by the input image processing part is formed, and the same processing is applied thereto.

【 0 1 4 2 】

Therefore, a distributed value as well as a mean within a range can be efficiently calculated.

【 0 1 4 3 】

(Embodiment 6)

This embodiment discloses a technique by which a bilaterally

symmetric image with respect to a template image can be efficiently processed.

【 0 1 4 4 】

This structure is shown in Fig. 19. That is, in addition to the structure of Fig. 1 of Embodiment 1, a symmetric vector generation unit 24 is provided between the recording unit 5 and the multiplication unit 10. As in Embodiment 1, Formula 8 is used as the similarity value formula in this embodiment.

【 0 1 4 5 】

Next, a description will be given of how to treat a bilaterally symmetric template image. For example, if the template image of Fig. 20(a) is an original image, a template image in which the original one has been bilaterally reversed is shown as in Fig. 20(b).

【 0 1 4 6 】

The relationship between the edge normal direction vectors of these template images is expressed by the following formula.

【Formula 20】

: Edge normal direction vector of image resulting from subjecting original template image to bilateral reversal

The evaluation vector of the template image that has been bilaterally reversed is expressed by the following formula.

【Formula 21】

Evaluation vector of

Evaluation vector of

Concerning Fourier transformation, because of the relation of Formula 22, Formula 23 is obtained by applying Formula 22 to Formula 21.

【Formula 22 】

【Formula 23 】

In detail, the evaluation vector of the template image that has been bilaterally reversed can be easily generated by, for example, reversing the positive and negative of the evaluation vector of the original template image.

【 0 1 4 7 】

Therefore, the evaluation vector of the template image that has been bilaterally reversed can be obtained only by allowing the symmetric vector generation unit 24 to apply Formula 23 to the evaluation vector of the original template image of the recording unit 5 in Fig. 19.

【 0 1 4 8 】

When simply assumed, there is no need to perform complex processing, such as a procedure in which the image of Fig. 20(b) is generated from the image of Fig. 20(a), and the evaluation vector is again calculated from the image of Fig. 20(b).

【 0 1 4 9 】

Thereby, the evaluation vector of the template image that has been bilaterally reversed can be generated without direct calculations, and processing speed can be improved. Additionally, recording capacity can be saved because the need to purposely store the template image that has been bilaterally reversed is obviated.

【 0 1 5 0 】

(Embodiment 7)

In this embodiment, eye/eyebrow extraction processing is added to the face extraction processing described in Embodiment 3.

【 0 1 5 1 】

As in Fig. 22(b), eyes/eyebrow candidate range can be roughly extracted from the input image of Fig. 22(a) according to the processing described in Embodiment 3.

【 0 1 5 2 】

Point biserial correlation coefficient filters shown in Fig. 23(a) through Fig. 23(d) are applied onto each point of the image of this eye/eyebrow candidate range, a map of point biserial correlation values is then formed, and points where the correlation value in the map become high are set as the eyes center point 3002 and as an eyebrow center point 3003, respectively.

【 0 1 5 3 】

The point biserial correlation coefficient η is defined by the following formula (reference; Multivariate Analysis Handbook, page 17, Modern Mathematics).

【Formula 24】

Overall range: addition of 1st range to 2nd range

Number of pixels of 1st range

n: Number of pixels of overall range

Average brightness level of 1st range

Average brightness level of 2nd range

S: Standard deviation of overall range

Value in $\sqrt{\quad}$ is constant when mask size is fixed.

Referring to Fig. 23(a) through Fig.23(d), Fig. 23(a) shows the positional relationship of all ranges, Fig. 23(b) shows an overall range mask, Fig. 23(c) shows a 1st range mask, and Fig. 23(d) shows a 2nd range mask.

【 0 1 5 4 】

If the filter shape according to this point biserial correlation coefficient is formed as shown in Fig. 23(a), it will be expected that the eyebrow center 3002 and the eye center 3003 can be extracted as shown in Fig. 22(c).

【 0 1 5 5 】

Next, filter processing according to the point biserial correlation coefficient will be described.

【 0 1 5 6 】

First, main components of Formula 24 are expressed by the following formula.

【Formula 25】

wherein,

M1: 1st range mask

M2: 2nd range mask

Ma: Overall range mask

I(x,y): Each pixel value of input image

The following formulas are obtained by subjecting each component to Fourier transformation.

【Formula 26】

【Formula 27】

【Formula 28】

wherein

In order to perform these processings, the structure of Fig. 21 is formed, for example. First, each mask of the overall range, the 1st range, and the 2nd range is subjected to Fourier transformation by the orthogonal transformation unit 51 through 53.

【 0 1 5 7 】

An input image and a result of the face extraction described in Embodiment 3 are input to the eye/eyebrow candidate range extraction unit 54 through the map processing unit 12. Based on these inputs, the eye/eyebrow candidate range extraction unit 54 extracts only the eye/eyebrow candidate range shown in Fig. 22(b) from Fig. 22(a). Data concerning this eye/eyebrow candidate range is subjected to Fourier transformation by an orthogonal transformation unit 55 without any changes, is then squared by a square unit 56, and is subjected to Fourier transformation by an orthogonal transformation unit 57.

【 0 1 5 8 】

Thereafter, data shown in Formula 27 is input through a multiplication unit 58 to an inverse orthogonal transformation unit 62 precedent to a η map forming unit 65. Likewise, data shown in Formula 26 is input to an inverse orthogonal transformation unit 63 through a multiplication unit 60, and data shown in Formula 28 is input to an inverse orthogonal transformation unit 64 through a multiplication unit 61. The input data is subjected to inverse Fourier transformation by the inverse orthogonal transformation unit 62 through 64, and is output to the η map forming unit 65.

【 0 1 5 9 】

Thereafter, the η map forming unit 65 performs a calculation according to Formula 24 when receiving the data from the inverse orthogonal transformation unit 62 through 64, and outputs a map $\eta(x,y)$ of the point biserial correlation coefficient.

【 0 1 6 0 】

The eye/eyebrow center extraction unit 66 extracts two points

having high values from the map $\eta(x,y)$ output by the η map forming unit 65, and outputs them as the eyes center and an eyebrow center, respectively.

【 0 1 6 1 】

In this structure, multiplication must be performed roughly $15 \times 15 \times N = 225N$ times, wherein " 15×15 " (pixels) is the filter size of Fig. 23(a), and N is the number of pixels of the input image.

【 0 1 6 2 】

In contrast, according to this embodiment, the number of product calculations is roughly $N + [(2\sqrt{\gamma} - 4)N + 4] \times 5 + 12N + N + N = 5N(2\sqrt{\gamma} - 1) + 20$ times. For convenience, the calculation of " $\sqrt{}$ " is assumed as equal to one multiplication processing.

【 0 1 6 3 】

That is, (calculation amount of this embodiment) < (calculation amount of the conventional technique) under the condition that γ is 22 or less.

【 0 1 6 4 】

Usually, a huge image in which N is 2^{22} or more is not used. Therefore, it is understood that the image processing of this embodiment is smaller in the number of calculation times than that of the conventional processing, and is performed faster than that of the conventional processing.

【 0 1 6 5 】

Thus, according to this embodiment, the point biserial correlation coefficient filter processing can be more efficiently performed.

【 0 1 6 6 】

The positions of other face parts, such as eye corners, mouth edges, nostrils, and irises, can be calculated by variously changing the masks shown in Fig. 23.

【 0 1 6 7 】

(Embodiment 8)

This embodiment discloses a technique for expanding the function of the face extraction according to Embodiment 3 and extracting a mouth

range, which is a facial organ, from a face image.

【 0 1 6 8 】

As described in Embodiment 3 with reference to Fig. 14, a mouth candidate range shown in Fig. 25(b) can be extracted from the input image of Fig. 25(a).

【 0 1 6 9 】

When the extracted mouth candidate range is projected onto the Y-axis (i.e., when the total h of pixel values is plotted along the X-axis), a graph roughly shown in Fig. 25(c) is obtained.

【 0 1 7 0 】

The total h is defined by the following formula.

【Formula 29】

$I(x,y)$: Each pixel value of input image

w : Width of mouth candidate range

$h(x,y)$: Projection value

In order to efficiently obtain this total by use of orthogonal transformation, a mask shown in Fig. 25(d) is prepared. Formula 29 can

be rewritten like the following formula, including this mask.

【Formula 30】

Mask

When this is subjected to Fourier transformation, the following formula is obtained.

【Formula 31】

That is, what is required to obtain this projection value is to subject the input image and the mask pattern to Fourier transformation, thereafter perform the calculation of Formula 31, and subject its result to inverse Fourier transformation. Thereby, the map "h(x,y)" of the projection value "h" can be obtained.

【 0 1 7 1 】

From the above result, it is desirable to form the structure of Fig. 24, for example. As shown in Fig. 24, the input image and the mask pattern are subjected to Fourier transformation by the orthogonal transformation unit 25 and 26, respectively.

【 0 1 7 2 】

Thereafter, the transformation value is multiplied by the multiplication unit 27, and is subjected to inverse Fourier transformation by the inverse orthogonal transformation unit 28. As a result, the map $h(x,y)$ of the projection value is obtained.

【 0 1 7 3 】

The obtained map $h(x,y)$ is developed by a projection data extraction unit 29, and a maximum point extraction unit 30 calculates two maximum points from this map, and outputs the range between these maximum points as mouth range.

【 0 1 7 4 】

The mask pattern can be, of course, beforehand subjected to Fourier transformation as in Embodiment 1, and, if so, a processing performance can be concentrated on the processing of the input image, and processing speed will be improved.

【 0 1 7 5 】

According to this embodiment, the position of the mouth, which is a facial organ, (more specifically, the positions of both the upper and lower

lips) can be accurately calculated.

【 0 1 7 6 】

(Embodiment 9)

This embodiment discloses a technique for expanding the function of the face extraction according to Embodiment 3, and applying predetermined processing to a face image according to first and second examples of this embodiment.

【 0 1 7 7 】

「First Example」

In this example, a digital watermark is embedded into an extracted face image. That is, the structure of Fig. 26 is formed. A result using part 600 is provided at the subsequent stage of the map processing unit 12 of Fig. 11.

【 0 1 7 8 】

The result-using part 600 includes a face image cutting-out unit 31 for separating an input image into a face image and a non-face image with reference to the input image and the face position that is determined by the

map processing unit 12. The face image part is output from the face image cutting-out unit 31 to a digital watermark embedding unit 32, and a predetermined digital watermark is embedded into the face image part. Herein, this digital watermark can be a well-known one.

【 0 1 7 9 】

On the other hand, the part excluding the face image is output from the face image cutting-out unit 31 directly to an image synthesizing unit 33.

【 0 1 8 0 】

The image synthesizing unit 33 combines the face image into which the digital watermark is embedded with the part excluding the face image, and outputs an image into which the digital watermark has been embedded.

【 0 1 8 1 】

Therefore, with respect to, for example, an input image of Fig. 27(a), an output image of Fig. 27(b) into a face part of which a digital watermark has been embedded is obtained.

【 0 1 8 2 】

The name of a model to be photographed or the date of the photograph is suitable as a digital watermark.

【 0 1 8 3 】

According to this example, watermark data can be concentratively and easily embedded into a face part that is liable to be falsified.

【 0 1 8 4 】

「Second Example」

In this example, specific editing is applied only to an extracted face image. That is, the structure of Fig. 28 is formed. A result-using part 601 is provided at the subsequent stage of the map processing unit 12 of Fig. 11.

【 0 1 8 5 】

The result-using part 601 includes the face image cutting-out unit 31 for separating an input image into a face image and a non-face image with reference to the input image and the face position that is determined by the map processing unit 12. The face image part is output from the

face image cutting-out unit 31 to an image correction unit 34, and predetermined editing is applied to the face image part. Herein, the editing can be a well-known one.

【 0 1 8 6 】

On the other hand, the part excluding the face image is output from the face image cutting-out unit 31 directly to the image synthesizing unit 33.

【 0 1 8 7 】

The image synthesizing unit 33 combines the face image that has been edited with the part excluding the face image, and outputs an edited image.

【 0 1 8 8 】

Therefore, referring to, for example, an input image of Fig. 29(a), an output image in which a face range has been extracted like Fig. 29(b), and only a face part has been edited like Fig. 29(c) is obtained.

【 0 1 8 9 】

In an image of a person photographed by counter light, an image of

the face part might be corrected so that a face color becomes whitish, because the face is too dark and is hard to see. However, in the editing by the image correction unit 34, such an image may be arbitrarily corrected.

【 0 1 9 0 】

According to this example, an image of only the face part can be easily and selectively corrected, or, in other words, image correction can be performed without exerting an influence on a part excluding the face.

【 0 1 9 1 】

[EFFECT OF THE INVENTION]

According to the present invention, patterns can be extracted stably and at high speed with less influence of the difference of the photographic condition and background.

【 0 1 9 2 】

Patterns of a plurality of templates can also be extracted at high speed.

【 0 1 9 3 】

The similarity value map can be amplified and a part similar to the template can be stably detected from the input image.

【 0 1 9 4 】

Attributes inside the image can be added to the similarity value, and can be processed more clearly and more efficiently.

【 0 1 9 5 】

Data of the template image that have been bilaterally reversed can be generated indirectly, and data amount of the template image can be reduced.

【 0 1 9 6 】

An object to be processed can be reduced rationally.

【 0 1 9 7 】

Point biserial correlation coefficient filters can extract the center point of eyes and eyebrows.

【 0 1 9 8 】

A mouth range, which is a facial organ can be specified accurately.

【 0 1 9 9 】

Watermark data can be concentratively embedded into a face part that is liable to the falsified.

【 0 2 0 0 】

An image only the face part can be selectively performed the image correction.

[DESCRIPTION OF DRAWINGS]

[Fig. 1]

Fig. 1 is a block diagram of an image processing apparatus according to Embodiment 1 of the present invention.

[Fig. 2]

Fig. 2 (a) is a view showing a template image.

Fig. 2 (b) is a view showing an edge extraction image (x component) of the template image.

Fig. 2 (c) is a view showing an edge extraction image (y component) of the template image.

[Fig. 3]

Fig. 3 is an explanatory drawing for explaining the compression processing of an evaluation vector.

[Fig. 4]

Fig. 4 (a) is a view showing an input image.

Fig. 4 (b) is a view showing an edge extraction image (x component) of the input image.

Fig. 4 (c) is a view showing an edge extraction image (y component) of the input image.

[Fig. 5]

Fig. 5 (a) is a view showing a map of similarity values.

Fig. 5 (b) is a view showing the input image.

[Fig. 6]

Fig. 6 is an explanatory drawing for explaining a positive/negative reversal of an inner product.

[Fig. 7]

Fig. 7 (a) is a view showing a template image.

Fig. 7 (b) is a view showing an input image.

[Fig. 8]

Figs. 8 (a) is a view showing a template image.

Figs. 8 (b) is a view showing a template image.

[Fig. 9]

Fig. 9 is a block diagram of an image processing apparatus according to Embodiment 2 of the present invention.

[Fig. 10]

Figs. 10 (a) is a graph showing conjugate properties.

Figs. 10 (b) is a graph showing conjugate properties.

[Fig. 11]

Fig. 11 (a) is a block diagram of a template image processing part according to Embodiment 3 (first example) of the present invention.

Fig. 11 (b) is a block diagram of a template image processing part according to Embodiment 3 (second example) of the present invention.

[Fig. 12]

Fig. 12 is a view showing an input image.

[Fig. 13]

Fig. 13 (a) is a view showing a template image.

Fig. 13 (b) is a view showing an edge extraction image.

Fig. 13 (c) is a view showing an enlargement/reduction template image.

Fig. 13 (d) is a view showing a template image.

Fig. 13 (e) is a view showing an edge extraction image.

Fig. 13 (f) is a view showing an enlargement/reduction template image.

[Fig. 14]

Fig. 14 is a view showing a face extraction result.

[Fig. 15]

Fig. 15 is a block diagram of an image processing apparatus according to Embodiment 4 of the present invention.

[Fig. 16]

Fig. 16 is a view showing a peak pattern.

[Fig. 17]

Fig. 17 is a block diagram of an image processing apparatus

according to Embodiment 5 of the present invention.

[Fig. 18]

Fig. 18 (a) is a view showing a template image.

Fig. 18 (b) is a view showing a mask pattern.

[Fig. 19]

Fig. 19 is a block diagram of an image processing apparatus according to Embodiment 6 of the present invention.

[Fig. 20]

Fig. 20 (a) is a view showing an original template image.

Fig. 20 (b) is a view showing a template image that has been subjected to a bilateral reversal.

[Fig. 21]

Fig. 21 is a block diagram of a part of the image processing apparatus according to Embodiment 6 of the present invention.

[Fig. 22]

Fig. 22 (a) is a view showing an input image.

Fig. 22 (b) is a view showing the eyes/eyebrow candidate range.

Fig. 22 (c) is a view showing a recognition result.

[Fig. 23]

Fig. 23 (a) is a view showing a filter shape according to Embodiment 7 of the present invention.

Fig. 23 (b) is an explanatory drawing of an overall range mask.

Fig. 23 (c) is an explanatory drawing of a range-1 mask.

Fig. 23 (d) is an explanatory drawing of a range-2 mask.

[Fig. 24]

Fig. 24 is a block diagram of a part of an image processing apparatus according to Embodiment 8 of the present invention.

[Fig. 25]

Fig. 25 (a) is a view showing an input image.

Fig. 25 (b) is an explanatory drawing of a mouth candidate range.

Fig. 25 (c) is a graph of projection values.

Fig. 25 (d) is an explanatory drawing of a mask pattern.

Fig. 25 (e) is a view showing a projection-value map image.

Fig. 25 (f) is a graph of projection values.

[Fig. 26]

Fig. 26 is a block diagram of a part of an image processing apparatus according to Embodiment 9 (first example) of the present invention.

[Fig. 27]

Fig. 27 (a) is a view showing an input image.

Fig. 27 (b) is a view showing an output image.

[Fig. 28]

Fig. 28 is a block diagram of a part of the image processing apparatus according to Embodiment 9 (second example) of the present invention.

[Fig. 29]

Figs. 29 (a) is a view showing an input image.

Figs. 29 (b) is a view showing an output image.

[DESCRIPTION OF SYMBOLS]

- 1 edge extraction unit
- 2 evaluation vector generation unit

- 3 orthogonal transformation unit
- 4 compression unit
- 5 recording unit
- 6 edge extraction unit
- 7 evaluation vector generation unit
- 8 orthogonal transformation unit
- 9 compression unit
- 10 multiplication unit
- 11 inverse orthogonal transformation unit
- 12 map processing unit
- 13 conjugate compression unit
- 14 conjugate reconstruction unit
- 15 enlargement/reduction unit
- 16 addition unit
- 17 orthogonal transformation unit
- 18 compression unit
- 19 recording unit

- 20 mask pattern generation unit
- 21 orthogonal transformation unit
- 22 compression unit
- 23 recording unit
- 24 symmetric vector generation unit
- 25,26 orthogonal transformation unit
- 27 multiplication unit
- 28 inverse orthogonal transformation unit
- 29 projection data extraction unit
- 30 maximum point extraction unit
- 31 face image cutting-out unit
- 32 digital watermark embedding unit
- 33 image synthesizing unit
- 601 result-using part
- 34 image correction unit
- 51 orthogonal transformation unit
- 52 orthogonal transformation unit

- 53 orthogonal transformation unit
- 54 eye/eyebrow candidate range extraction unit
- 55 orthogonal transformation unit
- 56 square unit
- 57 orthogonal transformation unit
- 58 multiplication unit
- 59 reduction unit
- 60 multiplication unit
- 61 multiplication unit
- 62,63,64 inverse orthogonal transformation unit
- 65 η map forming unit
- 66 eye/eyebrow center extraction unit
- 100 template image processing part
- 101,102 template image processing part
- 200 input image processing part
- 300 peak pattern processing part
- 400 mask pattern processing part

500 projection image processing part

600 result-using part

[DOCUMENT NAME] ABSTRACT

[ABSTRACT]

[PROBLEM TO BE SOLVED] It is an object of the present invention to provide an image processing method and an image processing apparatus capable of obtaining an accurate, clear recognition result and capable of performing high speed processing.

[SOLUTION] An image processing method for detecting an object from an input image by use of a template image. The image processing method includes a step of inputting a specified image with respect to both a template image and an input image, a step of calculating an edge normal direction vector of the specified image, a step of generating an evaluation vector from the edge normal direction vector, a step of subjecting the evaluation vector to orthogonal transformation, a step of performing a product sum calculation of corresponding spectral data with respect to each evaluation vector that has been subjected to orthogonal transformation and has been obtained for each of the template image and the input image, and a step of subjecting it to inverse orthogonal

transformation and generating a similarity value map. The formula of the similarity value, the orthogonal transformation, and the inverse orthogonal transformation each have linearity. It is possible to make pattern recognition in which the component of the similarity value is not subjected to positive/negative reversal through variations in brightness of its background.

[SELECTED FIGURE] Fig. 1

Fig.1

template image→1 edge extraction

2,7 evaluation vector generation

4,9 compression

5 recording

input image→6 edge extraction

11 inverse FFT

12 map processing→result

Fig.2(a)

template image

Fig.2(b)

X component

Fig.2(c)

Y component

Fig.3

object to be processed

Fig.4(a)

input image

Fig.4(b)

X component

Fig.4(c)


Y component

Fig.5(a)

maximum value

Fig.7(a)(b)

background



specified object

template image input image

Fig.9

template image → 1 edge extraction

2,7 evaluation vector generation

4,9 compression

5 recording

input image → 6 edge extraction

11 inverse FFT

12 map processing → result

13 conjugate compression

14 conjugate restoring

Fig.11(a)

1 edge extraction

2 evaluation vector generation

4 compression

5 recording

template image → 15 enlargement/reduction

Fig.11(b)

1 edge extraction

2 evaluation vector generation

4 compression

5 recording

template image→15 enlargement/reduction

Fig.15

template image→1 edge extraction

2,7 evaluation vector generation

4,9,18 compression

5,19 recording

input image→6 edge extraction

11 inverse FFT

12 map processing→result

peak pattern P→17 FFT

Fig.17

template image→1 edge extraction

2,7 evaluation vector generation

4,9,22 compression

5,23 recording

input image→6 edge extraction

11 inverse FFT

12 map processing→result

20 mask pattern generation

Fig.18(a)

template image

Fig.18(b)

mask pattern q

value 0 part

value $1/N$ part

Fig.19

template image→1 edge extraction

2,7 evaluation vector generation

4,9 compression

5 recording

input image→6 edge extraction

11 inverse FFT

12 map processing→result

24 symmetric vector generation

Fig.21

overall range mask(Ma)

1st range mask(M1)

2nd range mask(M2)

12 map processing

input image→54 eye/eyebrow candidate range extraction

56 square

62,63,64 inverse FFT

65 η map forming

66 eye/eyebrow center extraction→center position

Fig.23(a)

don't care

1st range

2nd range

1st range

Fig.23(b)

overall mask(Ma)

Fig.23(c)

1st range mask(M1)

Fig.23(d)

2nd range mask(M2)

Fig.24

input image→25 FFT

mask pattern →26 FFT

28 inverse FFT

29 projection data extraction

30 maximum point extraction→mouth range output

Fig.25(c)

maximum point

mouth range

projection value

Fig.25(d)

value 0

value 1

Fig.25(e)

mouth candidate position

Fig.25(f)

maximum point

mouth range

projection value

Fig.26

12 map processing→result output face position

input image→31 face image cutting-out

face image→32 digital watermark embedding

non-face image→33 image synthesizing

Fig.27(b)

digital watermark embedded part

Fig.28

12 map processing→result output face position

input image→31 face image cutting-out

face image→34 image correction

non-face image→33 image synthesizing

Fig.29(b)

detected face range



Certificate of Accuracy of Translation

The undersigned,

Maki NAKAMURA

certifies:

- (1) I am fully conversant with both the English and the Japanese languages;
- (2) I have translated into English:
Japanese Patent Application SN 2001 - 120496
- (3) The translation is, to the best of my knowledge and belief, an accurate translation from the original into the English language.

Date: 20 / 11 / 2002
(Day / Month / Year)

Signature: Maki Nakamura

[DOCUMENT NAME] REQUEST FOR GRANT OF A PATENT

[REFERENCE NUMBER] 2038630002

[DATE OF FILING] April 19, 2001

[TO:] Commissioner of the Patent Office

[IPC] H04N 7/14

H04N 5/225

H04N 5/262

[INVENTOR]

[ADDRESS] c/o Matsushita Electric Industrial Co., Ltd., 1006,
Ooaza Kadoma, Kadoma-Shi, Osaka

[NAME] Kazuyuki IMAGAWA

[INVENTOR]

[ADDRESS] c/o Matsushita Electric Industrial Co., Ltd., 1006,
Ooaza Kadoma, Kadoma-Shi, Osaka

[NAME] Tetsuya YOSHIMURA

[INVENTOR]

[ADDRESS] c/o Matsushita Electric Industrial Co., Ltd., 1006,

Ooaza Kadoma, Kadoma-Shi, Osaka

[NAME] Katsuhiko IWASA

[INVENTOR]

[ADDRESS] c/o Matsushita Electric Industrial Co., Ltd., 1006,

Ooaza Kadoma, Kadoma-Shi, Osaka

[NAME] Hideaki MATSUO

[INVENTOR]

[ADDRESS] c/o Matsushita Electric Industrial Co., Ltd., 1006,

Ooaza Kadoma, Kadoma-Shi, Osaka

[NAME] Yuji TAKATA

[APPLICANT]

[ID] 000005821

[NAME] Matsushita Electric Industrial Co., Ltd.

[AGENT]

[ID] 100097179

[PATENT ATTORNEY]

[NAME] Kazuyuki HIRANO

[PRIORITY CLAIM BASED ON EARLIER APPLICATION]

[NUMBER OF EARLIER APPLICATION] 2001-25098

[FILING DATE OF EARLIER APPLICATION] February 1, 2001

[INDICATION OF FEE]

[NUMBER OF PREPAID LEDGER] 058698

[FEE] 21000

[LIST OF ENCLOSURES]

[ITEM]	Specification	1
--------	---------------	---

[ITEM]	Drawing	1
--------	---------	---

[ITEM]	Abstract	1
--------	----------	---

[NUMBER OF GENERAL POWER OF ATTORNEY] 0013529

[PROOF] Required

[DOCUMENT NAME] SPECIFICATION

[TITLE OF THE INVENTION] IMAGE PROCESSING METHOD
AND APPARATUS

[CLAIMS]

[Claim1] An image processing method for evaluating matching between a template image and an input image by use of a similarity value map,

the method including a step of generating an evaluation vector for each of the template image and the input image, wherein the evaluation vector includes a component in which an edge normal direction vector of a specified image undergoes even-numbered times angular transformation.

[Claim2] An image processing method comprising:

a step of inputting a specified image for both a template image and an input image and calculating an edge normal direction vector of the specified image;

a step of generating an evaluation vector from the edge normal direction vector;

a step of subjecting the evaluation vector to orthogonal transformation;

a step of performing a product sum calculation of corresponding spectral data for each evaluation vector that has been subjected to orthogonal transformation and has been obtained for the template image and input image; and

a step of subjecting a result of the product sum calculation to inverse orthogonal transformation and generating a map of similarity values;

wherein a formula of the said similarity values, the said orthogonal transformation, and the said inverse orthogonal transformation each have linearity.

[Claim3] The image processing method of Claim 2, further comprising a step of compressing each evaluation vector that has been subjected to orthogonal transformation so as to reduce a processing amount.

[Claim4] The image processing method of Claim 2 to 3, wherein for the template image, the steps taken until the evaluation vector that has

been subjected to orthogonal transformation is compressed are executed before the input image is input, and its result is stored in a recording means.

[Claim5] The image processing method of Claim 2 to 4, wherein the evaluation vector is normalized with respect to a vector length.

[Claim6] The image processing method of Claim 2 to 5, wherein the evaluation vector of the template image is normalized by the number of edge normal direction vectors.

[Claim7] The image processing method of Claim 2 to 6, wherein a data amount is reduced by use of complex conjugate properties of orthogonal transformation before performing a product sum calculation, and the data amount is restored after performing the product sum calculation.

[Claim8] The image processing method of Claim 2 to 7, wherein the template image is enlarged/reduced to various sizes, and the evaluation vector of each size is subjected to addition processing.

[Claim9] The image processing method of Claim 8, wherein for the template image, the addition processing of the evaluation vector is carried

out after executing the step of compressing each evaluation vector so as to reduce the processing amount.

[Claim10] The image processing method of Claim 2 to 9, wherein the template image is an image of a typified face.

[Claim11] The image processing method of Claim 2 to 10, wherein a peak pattern that makes a peak of the similarity value steep is prepared, and a result obtained by subjecting data of this peak pattern to orthogonal transformation is applied to the product sum calculation.

[Claim12] The image processing method of Claim 2 to 10, wherein a mask pattern that depends on the template image is formed, and a result obtained by subjecting data of this mask pattern to orthogonal transformation is applied to the product sum calculation.

[Claim13] The image processing method of Claim 12, wherein the said mask pattern shows an average of a number of pixels in an image of the template image.

[Claim14] The image processing method of Claim 2 to 12, further comprising a step of, for the template image, processing positive and

negative signs of the evaluation vector of the original template image and generating an evaluation vector of a bilaterally symmetrical image with respect to the original template image, by which the generated evaluation vector is applied to the product sum calculation.

[Claim15] The image processing method of Claim 10, wherein a map of point biserial correlation coefficients is generated on the basis of an extracted face image, and a position of the face part is calculated.

[Claim16] The image processing method of Claim 10, wherein a distribution of projection values in a y-direction is calculated on the basis of the extracted face image by use of the mask pattern, and two maximum points are calculated from this distribution, and an range between these maximum points is output as a mouth range.

[Claim17] The image processing method of Claim 10, wherein the input image is divided into only the face image and parts other than the face image on the basis of the extracted face image, and a digital watermark is embedded only into the face image, and the face image into which the digital watermark has been embedded and parts other than the

face image are combined together and are output.

[Claim18] The image processing method of Claim 10, wherein the input image is divided into only the face image and parts other than the face image on the basis of the extracted face image, and only the face image is edited, and the face image that has been edited and parts other than the face image are combined together and are output.

[Claim19] An image processing apparatus comprising:

a template image processing part for inputting a template image and calculating an edge normal direction vector of the template image, generating an evaluation vector from the edge normal direction vector, subjecting the evaluation vector to orthogonal transformation, and compressing the evaluation vector that has been subjected to the orthogonal transformation so as to reduce the processing amount;

an input image processing part for inputting an input image and calculating an edge normal direction vector of the input image, generating an evaluation vector from the edge normal direction vector, subjecting the evaluation vector to orthogonal transformation, and compressing the

evaluation vector that has been subjected to the orthogonal transformation so as to reduce the processing amount;

multiplication means for performing a product sum calculation of corresponding spectral data about each evaluation vector that has been subjected to the orthogonal transformation and has been obtained for the template image and the input image; and

inverse orthogonal transformation means for subjecting a result of the product sum calculation to inverse orthogonal transformation and generating a map of similarity values;

wherein the evaluation vector includes a component in which an edge normal direction vector of a specified image undergoes even-numbered times angular transformation, and a formula of the similarity values, the orthogonal transformation, and the inverse orthogonal transformation each have linearity.

[Claim20] The image processing apparatus of Claim 19, wherein the said template image processing part is provided with a recording means for recording the evaluation vector that has been compressed to reduce a

processing amount and that has been subjected to orthogonal transformation, and

a result obtained by compressing the evaluation vector that has been subjected to orthogonal transformation is stored in the recording means before inputting the input image.

[Claim21] The image processing apparatus of Claim 19, further comprising: a conjugate compression means, provided between the said recording means and the said multiplication means, for reducing the data amount by use of complex conjugate properties of orthogonal transformation; and

a conjugate restoring means, provided between the said multiplication means and the said inverse orthogonal transformation means, for restoring the data amount reduced by use of the complex conjugate properties of orthogonal transformation.

[Claim22] The image processing apparatus of Claim 19 to 21, further comprising: an enlargement/reduction means for enlarging/reducing the template image to various sizes; and an addition means for performing

addition processing of the evaluation vector of each size.

[Claim23] The image processing apparatus of Claim 22, wherein the said addition means performs addition processing of the evaluation vector of the template image after compressing the vector so as to reduce the processing amount.

[Claim24] The image processing apparatus of Claim 19, further comprising a peak pattern processing part for subjecting a peak pattern by which a peak of a similarity value is made steep to orthogonal transformation and compressing the peak pattern that has been subjected to the orthogonal transformation so as to reduce the processing amount, wherein a result obtained by subjecting data of this peak pattern to the orthogonal transformation is applied to a product sum calculation of the said multiplication means.

[Claim25] The image processing apparatus of Claim 19, further comprising a mask pattern processing part for forming a mask pattern that depends on the template image and generating data obtained by subjecting data of this mask pattern to orthogonal transformation and by compressing

it,

wherein a processing result of the said mask pattern processing part is applied to a product sum calculation of the said multiplication means.

[Claim26] The image processing apparatus of Claim 25, wherein the said mask pattern shows a mean of the number of pixels inside an image of the template image.

[Claim27] The image processing apparatus of Claim 20, further comprising a symmetric vector generation means for processing positive and negative signs of the evaluation vector of an original template image recorded in the said recording means, and generating an evaluation vector of a bilaterally symmetric image with respect to the original template image,

wherein the evaluation vector generated by the symmetric vector generation means is applied to a product sum calculation of the said multiplication means.

[Claim28] The image processing apparatus of Claim 19, further comprising a η map forming means for forming a map of a point biserial

correlation coefficient on the basis of an extracted face image, and an extraction means for calculating a position of a face part from the formed map.

[Claim29] The image processing apparatus of Claim 19, further comprising a maximum point extraction means for calculating a projection value distribution in a y direction by use of a mask pattern on the basis of an extracted face image, and calculating two maximum points from this distribution, and outputting a range between the maximum points such as a mouth range.

[Claim30] The image processing apparatus of Claim 19, further comprising: a face image cutting-out means for separating an input image into only a face image and parts excluding the face image on the basis of an extracted face image; a digital watermark embedding means for embedding a digital watermark only into the face image; and an image synthesizing means for combining the face image into which the digital watermark has been embedded with parts excluding the face image and outputting them.

[Claim31] The image processing apparatus of Claim 19, comprising a face image cutting-out means for separating an input image into only a face image and parts excluding the face image on the basis of an extracted face image; an image edge correction means for editing only the face image; and an image synthesizing means for combining an edited face image with parts excluding the face image and outputting them.

[Claim32] The image processing method of Claim 10, further comprising: a step of cutting out a face image from the input image on the basis of an extracted face image; a step of extracting a facial inner image from the face image that has been cut out; a step of calculating a feature that serves to correct the face image on the basis of the extracted face image; a step of determining a correction function on the basis of the obtained feature; and a step of applying image correction based on the determined correction function at least onto the face image that has been cut out.

[Claim33] The image processing method of Claim 32, wherein the said feature is a combination of two or more of brightness, chroma average, or

hue average.

[Claim34] The image processing apparatus of Claim 19, further comprising: face image cutting-out means for cutting out a face image from the input image on the basis of an extracted face image; face internal range extraction means for extracting a facial inner image from the face image that has been cut out; image feature extraction means for calculating a feature that serves to correct the face image on the basis of the extracted face image; correction function determining means for determining a correction function on the basis of the obtained feature; and image correction means for applying image correction based on the determined correction function at least onto the face image that has been cut out.

[Claim35] The image processing apparatus of Claim 34, wherein the said feature is a combination of two or more of brightness, chroma average, or hue average.

[DETAILED DESCRIPTION]

【 0 0 0 1 】

[TECHNICAL FIELD]

The present invention relates to an image processing method for detecting an object from an input image by use of a template image, and relates to an image processing apparatus therefor.

【 0 0 0 2 】

[PRIOR ART]

Conventionally, a technique is well known in which a template image is pre-registered, and the position in an input image of an image similar to the template image is detected by pattern matching between the input image and the template image.

【 0 0 0 3 】

However, since distorted perceptions are liable to be shaped according to how the background of the image similar to the template image is formed, Japanese Published Unexamined Patent Application No. Hei-5-28273 discloses a technique that has been developed to solve this problem.

【 0 0 0 4 】

In this publication, a similarity value between the template image

and the image corresponding to the template image is defined by the following mathematical formula.

【Formula 1】

Cv: Correlation coefficient (similarity value)

M: Number of pixels of template image in x direction

N: Number of pixels of template image in y direction

Sx: Derivative value of input image S in x direction

Sy: Derivative value of input image S in y direction

Tx: Derivative value of template image T in x direction

Ty: Derivative value of template image T in y direction

【 0 0 0 5 】

In detail, an inner product ($\cos\theta$) of an angle θ between a normal direction vector of the edge of the template image and a normal direction vector of the edge of the input image is a component of the similarity value.

【 0 0 0 6 】

[TECHNICAL PROBLEM]

However, there is a problem in that, as described later in detail, if the brightness of a background periphery of an image of an object is uneven, the positive and negative of the inner product are reversed, so that the similarity value becomes unsuitable for the real image, and distorted perceptions are easily produced, thus making it difficult to obtain a desirable recognition result.

【 0 0 0 7 】

Additionally, the similarity value formula is nonlinear with respect to the normal direction vectors of the edges of the input and template images, and processing for the template image and processing for the input image must be performed simultaneously.

【 0 0 0 8 】

Further, the template image is scanned on the input image, and a correlated calculation of the input image and the reference image must be performed for each scanning point, and therefore, in practicality, a resulting expanding calculation amount makes real-time processing impossible.

【 0 0 0 9 】

It is therefore an object of the present invention to provide an image processing method and an image processing apparatus capable of obtaining an accurate, clear recognition result and capable of performing high speed processing.

【 0 0 1 0 】

[MEANS]

In an image processing method according to a first aspect of the present invention, matching between a template image and an input image is evaluated by use of a similarity value map, and an evaluation vector is generated for each of the template and input images, and the evaluation vector includes a component in which a normal direction vector of an edge of a specified image undergoes even-numbered times angular transformation.

【 0 0 1 1 】

With this structure, an image processing method capable of obtaining a clear, accurate recognition result and capable of performing

high speed processing can be realized.

【 0 0 1 2 】

[EMBODIMENTS OF THE INVENTION]

In an image processing method according to a first aspect of the present invention, matching between a template image and an input image is evaluated by use of a similarity value map, and an evaluation vector is generated for each of the template and input images, and the evaluation vector includes a component in which a normal direction vector of an edge of a specified image undergoes even-numbered times angular transformation.

【 0 0 1 3 】

With this structure, the matching therebetween can be properly evaluated with no influence on the similarity value even in a case in which the positive and negative of an inner product ($\cos\theta$) of an angle θ between a normal direction vector of the edge of the template image and a normal direction vector of the edge of the input image are reversed because of unevenness in brightness of its background.

【 0 0 1 4 】

An image processing method according to a second aspect of the present invention includes a step of inputting a specified image for each of a template image and an input image and calculating a normal direction vector of an edge of the specified image; a step of generating an evaluation vector from the edge normal direction vector; a step of subjecting the evaluation vector to an orthogonal transformation; a step of performing a product sum calculation of corresponding spectral data for each evaluation vector, which has been subjected to orthogonal transformation, obtained for the template image and input image; and a step of subjecting a result of the product sum calculation to an inverse orthogonal transformation and generating a map of similarity values; in which a formula of the similarity values, the orthogonal transformation, and the inverse orthogonal transformation each have linearity.

【 0 0 1 5 】

With this structure, a Fourier transformation value of the template image and a Fourier transformation value of the input image do not need

to be simultaneously calculated. In other words, the Fourier transformation value of the template image can be obtained prior to that of the input image, thus making it possible to lighten the processing burden and improve processing speed.

【 0 0 1 6 】

An image processing method according to a third aspect of the present invention includes a step of compressing each evaluation vector, which has been subjected to the orthogonal transformation, so as to reduce the processing amount.

【 0 0 1 7 】

With this structure, what is processed is limited only to an effective component (e.g., low-frequency component), and processing speed can be improved.

【 0 0 1 8 】

In an image processing method according to a fourth aspect of the present invention, for the template image, the steps taken until the evaluation vector that has been subjected to the orthogonal transformation

is compressed are executed before the input image is input, and its result is stored in a recording unit.

【 0 0 1 9 】

With this structure, the processing relating to the template image is completed merely by reading from the recording unit, and processing speed can be improved.

【 0 0 2 0 】

In an image processing method according to a fifth aspect of the present invention, the evaluation vector is normalized with respect to a vector length.

【 0 0 2 1 】

With this structure, the stability of pattern extraction can be improved without undergoing length variations though the strength of the edge of the input image varies, and the vector length varies according to a photographic condition.

【 0 0 2 2 】

In an image processing method according to a sixth aspect of the

present invention, the evaluation vector of the template image is normalized by the number of edge normal direction vectors.

【 0 0 2 3 】

Therefore, independent of whether the number of edges of the template image is large or small, a similarity can be evaluated on the same scale by dividing it by n and normalizing it.

【 0 0 2 4 】

In an image processing method according to a seventh aspect of the present invention, a data amount is reduced by use of complex conjugate properties of an orthogonal transformation before performing a product sum calculation, and the data amount is restored after performing the product sum calculation.

【 0 0 2 5 】

With this structure, the data amount can be greatly reduced to improve processing speed, and memory capacity can be saved.

【 0 0 2 6 】

In an image processing method according to an eighth aspect of the

present invention, the template image is enlarged/reduced to various sizes, and the evaluation vector of each size is subjected to addition processing.

【 0 0 2 7 】

With this structure, matching does not need to be repeatedly carried out for each size, and processing speed can be improved.

【 0 0 2 8 】

In an image processing method according to a ninth aspect of the present invention, for the template image, the addition processing of the evaluation vector is carried out after executing the step of compressing each evaluation vector so as to reduce the processing amount.

【 0 0 2 9 】

With this structure, what is subjected to addition processing can be reduced, and processing speed can be improved.

【 0 0 3 0 】

In an image processing method according to a tenth aspect of the present invention, the template image is an image of a typified face.

【 0 0 3 1 】

With this structure, not only the total position of a face but also the partial position of a main face part, such as the eyes, nose, or mouth, can be recognized.

【 0 0 3 2 】

In an image processing method according to an 11th aspect of the present invention, a peak pattern that makes a peak of the similarity value steep is prepared, and a result obtained by subjecting data of this peak pattern to an orthogonal transformation is applied to the product sum calculation.

【 0 0 3 3 】

With this structure, a part similar to a template can be detected from the input image more clearly and stably while reflecting the peak pattern.

【 0 0 3 4 】

In an image processing method according to a 12th aspect of the present invention, a mask pattern that depends on the template image is formed, and a result obtained by subjecting data of this mask pattern to an

orthogonal transformation is applied to the product sum calculation.

【 0 0 3 5 】

With this structure, closer detection can be performed while adding attributes other than the shape of the template image.

【 0 0 3 6 】

In an image processing method according to a 13th aspect of the present invention, the mask pattern shows an average of a number of pixels in an image of the template image.

【 0 0 3 7 】

With this structure, attributes of the template image can be reflected by a simple mask pattern.

【 0 0 3 8 】

An image processing method according to a 14th aspect of the present invention further includes a step of, for the template image, processing positive and negative signs of the evaluation vector of the original template image and generating an evaluation vector of a bilaterally symmetrical image with respect to the original template image,

by which the generated evaluation vector is applied to the product sum calculation.

【 0 0 3 9 】

With this structure, the recording amount of the template image can be saved, and the evaluation vector of the template image that has been bilaterally reversed can be generated without direct calculation, thus making it possible to improve processing speed.

【 0 0 4 0 】

In an image processing method according to a 15th aspect of the present invention, a map of point biserial correlation coefficients is generated on the basis of an extracted face image, and a position of the face part is calculated.

【 0 0 4 1 】

With this structure, the position of the face part can be specified more accurately.

【 0 0 4 2 】

In an image processing method according to a 16th aspect of the

present invention, a distribution of projection values in a y-direction is calculated on the basis of the extracted face image by use of the mask pattern, and two maximum points are calculated from this distribution, and an extent between these maximum points is output as a mouth range.

【 0 0 4 3 】

With this structure, the mouth range can be specified more accurately.

【 0 0 4 4 】

In an image processing method according to a 17th aspect of the present invention, the input image is divided into only the face image and parts other than the face image on the basis of the extracted face image, and a digital watermark is embedded only into the face image, and the face image into which the digital watermark has been embedded and parts other than the face image are combined and output.

【 0 0 4 5 】

With this structure, watermark data can be concentratively embedded into the face part that is liable to be falsified.

【 0 0 4 6 】

In an image processing method according to an 18th aspect of the present invention, the input image is divided into only the face image and parts other than the face image on the basis of the extracted face image, and only the face image is edited, and the face image that has been edited and parts other than the face image are combined and output.

【 0 0 4 7 】

With this structure, only the face image can be corrected without exerting an influence on parts other than the face.

【 0 0 4 8 】

In an image processing method according to a 32nd aspect of the present invention, a face image is cut out from the input image on the basis of the extracted face image, a facial inner image is then extracted from the face image that has been cut out, a feature that serves to correct the face image is then calculated on the basis of the extracted face image, a correction function is then determined on the basis of the obtained feature, and image correction based on the determined correction function is

applied at least onto the face image that has been cut out.

【 0 0 4 9 】

With this structure, the face image is corrected according to the feature of only the facial inner image without being adversely affected by images that are not the face image, and therefore the viewability of the face image can be infallibly improved.

【 0 0 5 0 】

(Embodiment 1)

Referring to Fig. 1 through Fig. 8, the basic form of an image processing apparatus of the present invention will be described.

【 0 0 5 1 】

As shown in Fig. 1, the image processing apparatus according to Embodiment 1 includes two different processing parts, i.e., a template image processing part 100 and an input image processing part 200, and evaluates matching between a template image and an input image by use of a map of similarity values L. In this image processing apparatus, both the template image processing part 100 and the input image processing

part 200 perform orthogonal transformation with linearity, then perform multiplication, and calculate the similarity values L by inverse orthogonal transformation.

【 0 0 5 2 】

It should be noted that FFT (Fast Discrete Fourier Transformation) is used as an orthogonal transformation in all embodiments described later. However, not only FFT but also Hartley transformation or number theoretic transformation can be used, and "Fourier transformation" in the following description can be replaced by Hartley transformation or number theoretic transformation.

【 0 0 5 3 】

Further, both the template image processing part 100 and the input image processing part 200 employ an inner product of edge normal direction vectors so that a correlation becomes proportionately higher with proximity between the directions of the edge normal direction vectors. This inner product is evaluated by use of an even-numbered times angle expression. For convenience, only a double size angle will be hereinafter

described as an example of even-numbered times angle, but the same effect with the present invention can be produced in other even-numbered times angles such as a quadruple size or a sextuple size.

【 0 0 5 4 】

Next, the template image processing part 100 will be described. An edge extraction unit 1 applies differential processing (edge extraction) to a template image in x and y directions, and outputs an edge normal direction vector of the template image.

【 0 0 5 5 】

In this embodiment, a Sobel filter of 【Formula 2】 is used for the x direction, and a Sobel filter of 【Formula 3】 is used for the y direction.

【 0 0 5 6 】

An edge normal direction vector of the template image defined by the following formula is obtained with these filters.

【Formula 4】

【 0 0 5 7 】

This embodiment takes an example in which an image of a person in a specific posture who is walking through a pedestrian crossing is extracted from an input image of the vicinity of the pedestrian crossing.

【 0 0 5 8 】

The template image of the person is that of Fig. 2(a), for example. If the filter processing of Formula 2 is applied to the template image of Fig. 2(a), a result (x component) as shown in Fig. 2(b) will be obtained, and, if the filter processing of Formula 3 is applied to the template image of Fig. 2(a), a result (y component) as shown in Fig. 2(c) will be obtained.

【 0 0 5 9 】

An evaluation vector generation unit 2 inputs an edge normal direction vector of the template image from the edge extraction unit 1, and outputs the evaluation vector of the template image to an orthogonal transformation unit 3 through processings described later.

【 0 0 6 0 】

First, the evaluation vector generation unit 2 normalizes the length of the edge normal direction vector of the template image according to the

following formula.

【Formula 5】

【 0 0 6 1 】

Generally, the edge strength of the input image varies according to a photographic condition. However, an angular difference between the edges of the input and template images (or, a subordinate function value that varies according to this angular difference) is unsusceptible to the photographic condition.

【 0 0 6 2 】

Therefore, in the present invention, the edge normal direction vector of the input image is normalized to be 1 in length in the input image processing part 200, as described later. According to this, the edge normal direction vector of the template image is normalized to be 1 in length in the template image processing part 100.

【 0 0 6 3 】

As a result, the stability of pattern extraction can be improved. Usually, it is desirable to have a normalization length of 「1」, but other

constants can be used.

【 0 0 6 4 】

Concerning a trigonometric function, the following double size formula is established as is well known.

【Formula 6】

【 0 0 6 5 】

The evaluation vector generation unit 2 calculates the evaluation vector of the template image defined by the following formula.

【Formula 7】

When assumed to be a threshold (for fine edge removal), the evaluation vector V of the template image is:

if

else

wherein n is the number of $> a$.

【 0 0 6 6 】

Formula 7 will be described. The reason why a vector smaller than constant "a" is set as a 0 vector is to remove a noise, for example.

【 0 0 6 7 】

Next, a description will be given of the fact that x and y components of this evaluation vector are each divided by "n" for normalization.

【 0 0 6 8 】

Generally, the shape of the template image is arbitrary, and the shape of the edge is various. For example, there is a situation in which the number of edges is small as shown in Fig. 8(a), or the number of edges is larger (than that of Fig. 8(a)) as shown in Fig. 8(b). Therefore, in this embodiment, the similarity is intended to be evaluated on the same scale by dividing it by "n" for normalization independent of whether the number of the edges is small or large.

【 0 0 6 9 】

However, the normalizing processing of dividing it by "n" does not necessarily need to be performed, and normalizing processing can be omitted in a situation in which only one template image is used or in which only template images the same as the number of edges are used.

【 0 0 7 0 】

Next, a description will be given of the fact that the x and y components of Formula 7 serve as a subordination function of the cosine/sine for a double size of the x and y components of Formula 5.

【 0 0 7 1 】

If the inner product $\cos\theta$ of an angle θ between an evaluation vector T of the template image and an evaluation vector I of the input image is used as a similarity scale as in the conventional technique, the following problem will arise.

【 0 0 7 2 】

For example, let us suppose that the template image is that of Fig. 7(a), and the input image is that of Fig. 7(b). In the background of Fig. 7(b), the left background part of an image of a specified object is brighter than the image of the specified object, and the right background part of the image of the specified object is darker than the image of the specified object.

【 0 0 7 3 】

If considered only from the images, the images of the specified object completely coincide with each other when the center of the template image of Fig. 7(a) coincide with the center of the input image of Fig. 7(b), and therefore the similarity value must be the maximum at this time. Herein, if the edge normal direction vector that is directed outward from the image of the object is positive, the edge normal direction vector must be directed in the same direction (outward/inward) in the brighter background part of Fig. 7(b) and in the darker background part thereof when deriving from the image of the specified object.

【 0 0 7 4 】

However, if the brightness of the background of Fig. 7(b) is uneven in the right and left background parts with the specified object therebetween at this time, the directions are opposed as shown by arrows in Fig. 7(b) (i.e., outward from the specified object in the brighter background part, and inward from the specified object in the darker background part).

【 0 0 7 5 】

Originally, it is to reach the maximum similarity value, but the similarity value does not necessarily become high in this case, and thereby a distorted perception is easily shaped.

【 0 0 7 6 】

A detailed description of the above problem will be given with reference to Fig. 6. In the case an angle between the evaluation vector T of the template image and the evaluation vector I of the input image is represented as θ , and its inner product, i.e., $\cos\theta$ is used as a similarity value, the direction of the evaluation vector I of the input image has two possibilities, i.e., I of Fig. 6 and I' precisely opposite thereto because of unevenness in brightness of the background that exists in the periphery of the image of the specified object, as described above.

【 0 0 7 7 】

Therefore, the inner product used as a similarity scale will have two products, i.e., $\cos\theta$ and $\cos\theta'$.

【 0 0 7 8 】

Herein, $\theta + \theta' = \pi$, and $\cos\theta' = \cos(\pi - \theta) = -\cos\theta$.

【 0 0 7 9 】

Therefore, if $\cos\theta$ is used as the similarity scale, a similarity value will be oppositely reduced when there is a need to act properly to increase the similarity value, and the similarity value will be oppositely increased when there is a need to act properly to reduce the similarity value.

【 0 0 8 0 】

In other words, according to the prior art similarity value, matching between the template image and the input image cannot be correctly evaluated. As a result, disadvantageously, a wrong recognition is easily formed by the conventional technique, and a recognition result will not be clear even if images are shaped.

【 0 0 8 1 】

Therefore, in the present invention, a cosine that is a double size of θ , i.e., $\cos(2\theta)$ is used for the formula of the similarity value. Thereby, $\cos(2\theta') = \cos(2\theta)$ from the double size formula of Formula 6 even if $\cos\theta' = -\cos\theta$. In other words, the similarity value rises irrespective of the background when there is a need to act to increase the similarity value.

Therefore, the matching therebetween can be correctly evaluated in spite of the unevenness in brightness of the background. This applies to the quadruple size or the sextuple size as well as the double size.

【 0 0 8 2 】

Moreover, the properties of the similarity value monotonously decreasing with respect to angle θ do not change even if an even-numbered times angle cosine is used.

【 0 0 8 3 】

Therefore, according to the present invention, patterns can be stably extracted by an even-numbered times angle evaluation regardless of the brightness condition of the background.

【 0 0 8 4 】

More specifically, the similarity value is defined by the following formula in the present invention.

【Formula 8】

Similarity value

:Evaluation vector of input image

:Evaluation vector of template image

【 0 0 8 5 】

Since Formula 8 consists only of addition and multiplication, the similarity value is linear for each evaluation vector of the input and template images. Therefore, when Formula 8 is subjected to Fourier transformation, Formula 9 is obtained by a discrete correlation theorem of Fourier transformation (reference: Fast Fourier Transformation translated by Hiroshi Miyakawa published by Science and Technology).

【Formula 9】

Fourier transformation values of K_x, K_y

Fourier transformation complex conjugate of V_x, V_y

Hereinafter, Fourier transformation value represented as \sim , and complex conjugate represented as $*$.

【 0 0 8 6 】

The similarity value of Formula 8 is obtained by subjecting Formula 9 to inverse Fourier transformation. From careful consideration of Formula 9, the following two respects will become apparent.

【 0 0 8 7 】

First, (1) the Fourier transformation value of the template image and the Fourier transformation value of the input image can be simply multiplied together in a transformation value that has been subjected to orthogonal transformation.

【 0 0 8 8 】

Secondly, (2) the Fourier transformation value of the template image and the Fourier transformation value of the input image do not need to be simultaneously calculated, and the Fourier transformation value of the template image may be calculated prior to that of the input image.

【 0 0 8 9 】

Therefore, in this embodiment, the template image processing part 100 is provided with a recording unit 5 to record the output of a compression unit 4 before inputting the input image. Thereby, after the input image is input to the input image processing part 200, the template image processing part 100 has no need to process the template image, and the processing performance can be concentrated on processing subsequent

to the input image processing part 200 and a multiplication unit 10, thus making it possible to improve the processing speed.

【 0 0 9 0 】

Next, a description will be given of a structure subsequent to the evaluation vector generation unit 2. As shown in Fig. 1, in the template image processing part 100, the evaluation vector of the template image that is output from the evaluation vector generation unit 2 is subjected to Fourier transformation by the orthogonal transformation unit 3, and is output to the compression unit 4.

【 0 0 9 1 】

The compression unit 4 compresses the evaluation vector that has been subjected to Fourier transformation, and stores it in the recording unit 5. As shown in Fig. 3, the evaluation vector subjected thereto includes various frequency components in both x and y directions. By experiments carried out by the present inventors, it is known that sufficient accuracy can be obtained by processing the low frequency components (e.g., halves on the low frequency side in the x and y directions,

respectively) without processing all of the frequency components. In Fig. 3, the range $(-a \leq x \leq a, -b \leq y \leq b)$ having no oblique line is an original one, and the range $(-a/2 \leq x \leq a/2, -b/2 \leq y \leq b/2)$ having oblique lines is the one that has been compressed. That is, the processing amount becomes 1/4 times as much as before.

【 0 0 9 2 】

Thereby, an object to be processed can be compressed, and the processing speed can be improved.

【 0 0 9 3 】

The compression unit 4 and the recording unit 5 can be omitted when a data amount is small, or high-speed processing is not required.

【 0 0 9 4 】

Next, the input image processing part 200 will be described. The input image processing part 200 performs almost the same processing as the template image processing part 100. That is, according to Formula 2 and Formula 3, the edge extraction unit 6 outputs an edge normal direction vector of the input image defined by the following formula.

【Formula 10】

Edge normal direction vector of input image)

I_x: Derivative value of input image in x direction

I_y: Derivative value of input image in y direction

$$\begin{bmatrix} 0 & 0 & 9 & 5 \end{bmatrix}$$

The evaluation vector generation unit 7 inputs the edge normal direction vector of the input image from the edge extraction unit 6, and outputs an evaluation vector of the input image defined by the following two formulas.

【Formula 11】

Length normalized vector of input image)

【Formula 12】

When assumed to be a threshold (for fine edge removal), the evaluation vector K of the input image is:

if

else

$$\begin{bmatrix} 0 & 0 & 9 & 6 \end{bmatrix}$$

The input image processing part 200 differs from the template image processing part 100 only in the fact that normalizing processing of the division by "n" is not performed. In other words, evaluation by the even-numbered times angle, the normalizing processing to 1 in length, and the noise removal processing are performed in the same way as in the template image processing part 100.

【 0 0 9 7 】

Next, a structure subsequent to the evaluation vector generation unit 7 will be described. As shown in Fig. 1, in the input image processing part 200, the evaluation vector of the input image that is output from the evaluation vector generation unit 7 is subjected to Fourier transformation by the orthogonal transformation unit 8, and is output to the compression unit 9.

【 0 0 9 8 】

The compression unit 9 compresses the evaluation vector that has been subjected to Fourier transformation, and outputs it to the multiplication unit 10. Herein, the compression unit 9 compresses the

object to be processed to the same frequency band as the compression unit 4 (e.g., halves on the low frequency side in the x and y directions, respectively, in this embodiment).

【 0 0 9 9 】

The compression unit 9 can be, of course, omitted when the data amount is small, or when high-speed processing is not required, and the compression unit 9 is likewise omitted when the compression unit 4 is omitted in the template image processing part 100.

【 0 1 0 0 】

Next, the multiplication unit 10 and other construction subsequent to this will be described. When the processing in the template image processing part 100 and in the input image processing part 200 is completed, the multiplication unit 10 inputs a Fourier transformation value of each evaluation vector of the template and inputs images from the recording unit 5 and the compression unit 9.

【 0 1 0 1 】

Thereafter, the recording unit 5 performs a product-sum-calculation

according to Formula 9, and outputs the result (i.e., Fourier transformation value of the similarity value L) to an inverse orthogonal transformation unit 11.

【 0 1 0 2 】

The inverse orthogonal transformation unit 11 subjects the Fourier transformation value of the similarity value L to inverse Fourier transformation, and outputs the map $L(x,y)$ of the similarity value L to a map processing unit 12. The map processing unit 12 extracts a high-value point (peak) from the map $L(x,y)$, and outputs its position and its value. The map processing unit 12 and the construction subsequent to this can be freely arranged if necessary.

【 0 1 0 3 】

Next, a processing example by the template image of Fig. 2 will be described with reference to Fig. 4 and Fig. 5. If the input image is as shown in Fig. 4(a), the edge extraction unit 6 extracts an edge component in the x direction as shown in Fig. 4(b), and extracts an edge component in the y direction as shown in Fig. 4(c).

【 0 1 0 4 】

As a result of the aforementioned processing, a similarity value map $L(x,y)$ shown in Fig. 5(a) is obtained. Herein, the front end of the arrow indicated as the "maximum value" is a peak of this map, and, as is apparent from a comparison with the input image of Fig. 5(b), it is understood that the correct point can be clearly recognized by only one point.

【 0 1 0 5 】

In the conventional technique, the calculation must be performed by the number of times of the product, i.e., $2AB$ in order to successively scan the template image on input images and to obtain proof of Formula 1 at each position, wherein the size of the input image is $A(=2\gamma)$ and the size of the template image is B . Herein, the number of calculations is evaluated by the number of times of the product with high calculation costs.

【 0 1 0 6 】

In contrast, in this embodiment, FFT is performed twice by the orthogonal transformation unit 3 and 8, the product sum calculation is then

performed by the multiplication unit 10, and inverse FFT is performed once by the inverse orthogonal transformation unit 11. The number of calculations is merely the number of times of the product of $3\{(2\gamma-4)A+4\}+2A$.

【 0 1 0 7 】

In a comparison of the number of calculations therebetween, the number of calculations of the product according to this embodiment becomes about 1/100 of the number of calculations of the product according to the conventional technique, if $A=256\times 256=2^{16}$, and $B=60\times 60$. As a result, unusually high-speed processing can be carried out.

【 0 1 0 8 】

The discrete correlation theorem of Fourier transformation cannot be used in such a nonlinear formula as Formula 1 of the conventional technique.

【 0 1 0 9 】

Therefore, in the conventional technique, processing for the template image cannot be performed prior to that for the input image as

shown in Fig. 1 of this embodiment. In other words, in the conventional technique, both the template image and the input image must be simultaneously processed. Also in this respect, the processing speed in this embodiment becomes higher than that in the conventional technique.

【 0 1 1 0 】

(Embodiment 2)

In this embodiment, a conjugate compression unit 13 and a conjugate restoring unit 14 are added to the elements of Fig. 1 as shown in Fig. 9. The conjugate compression unit 13 further halves the Fourier transformation value of the evaluation vector of the template image that has been read from the recording unit 5 by use of complex conjugate properties of Fourier transformation.

【 0 1 1 1 】

This respect will be described. The following formula is established for the spectrum obtained by real number Fourier transformation.

【Formula 13】

【 0 1 1 2 】

In detail, a spectral value at a specific point is equal to the complex conjugate of a spectral value at a position symmetrical to that point in a uv coordinate system. Use of this property makes it possible to reduce the processing amount by half of the uv coordinate system as shown in Fig. 10(a).

【 0 1 1 3 】

Since the compression unit 4 and the compression unit 9 further compress it, the data amount can be reduced to 1/8 of the original data as shown in Fig. 10(b). Therefore, the processing speed can be improved, and memory capacity can be saved.

【 0 1 1 4 】

As a result, in this embodiment, the Fourier transformation value that the conjugate compression unit 13 has read from the recording unit 5 is halved, and is output to the multiplication unit 10. Thereafter, the conjugate reconstruction unit 14 performs processing by which the output from the multiplication unit 10 is doubled, and outputs it to the inverse

orthogonal transformation unit 11.

【 0 1 1 5 】

These constitute the basis of the present invention. A useful technique will be hereinafter disclosed by application of this basis.

【 0 1 1 6 】

(Embodiment 3)

In this embodiment, a first example and a second example will be described. A technique for performing face extraction by using an enlarged/reduced template image is disclosed in either example. According to this technique, processing by use of similar templates different in size can be carried out efficiently and at high speed. The application of this technique is not limited only to face extraction.

【 0 1 1 7 】

「First Example」

Fig. 11(a) is a block diagram of a template image processing part according to Embodiment 3 (first example) of the present invention. Some modifications have been made to the template image processing part

100 of Fig. 1 or Fig. 9 as shown in the figure.

【 0 1 1 8 】

First, when a template image is input to a template image processing part 101, the image is enlarged/reduced by a enlargement/reduction unit 15. Thereafter, the enlarged/reduced template image is output to an edge extraction unit 1.

【 0 1 1 9 】

When an evaluation vector generation unit 2 outputs the evaluation vector of the template image, an addition unit 16 applies addition processing to this, and data obtained by the addition processing is output to an orthogonal transformation unit 3.

【 0 1 2 0 】

The addition unit 16 performs addition processing for each size range according to the following formula.

【Formula 14】

Evaluation vector of template image

wherein the size range is $a \sim b$.

【 0 1 2 1 】

Although image processing is carried out by use of one template image in Embodiments 1 and 2, templates with multiple sizes are processed by use of a plurality of templates in this embodiment.

【 0 1 2 2 】

Moreover, the sizes of the templates are each separated into a specific range, and a template processing result is superimposed thereon.

【 0 1 2 3 】

Fig. 12 shows an example of an input image that includes a face image of a person. In this example, a template image of a straight face, such as that of Fig. 13(a), is prepared. A template image of a face inclined at a specific angle as shown in Fig. 13(d) is further prepared. The degree to which the face to be prepared is inclined can be appropriately selected.

【 0 1 2 4 】

When the edges of the template images of Figs. 13(a) and 13(d) are extracted, appearances shown in Fig. 13(b) and 13(e), respectively, are

obtained in this embodiment. Further, when the image of Fig. 13(a) or 13(d) is input, an evaluation vector corresponding to the edge image is generated as shown in Fig. 13(c) or 13(f).

【 0 1 2 5 】

As in Embodiments 1 and 2, data concerning the template images are stored in the recording unit 5.

【 0 1 2 6 】

When the input image is input, a procedure subsequent to those of the input image processing part 200 and the multiplication unit 10 is performed in the same way as in Embodiments 1 and 2.

【 0 1 2 7 】

Corresponding similarity value maps are calculated for superimposed template data of all size ranges of the template images.

【 0 1 2 8 】

Thereby, a detection result, such as that shown in Fig. 14, is obtained. As is apparent from Fig. 14, not only the overall position of the face but also its size and the positions of the main face parts, such as the

eyes, nose, and mouth, can be recognized.

【 0 1 2 9 】

At this time, it is desirable to display the processing result on a display or to output it to a printer as shown in Fig. 14 in the stage subsequent to the map processing unit 12.

【 0 1 3 0 】

According to First Example, the following effects can be obtained.

(1) Even if template data in a specific size range is added, and image processing is performed with layered templates, a part similar to the template often shows a high similarity value. Therefore, when similarity values of all sizes are calculated, the processing of the product sum calculation part and the processing of the inverse orthogonal transformation part must be repeatedly performed NM times, wherein N is the number of the templates, and M is the number of all sizes. On the other hand, the number of processings reaches NM/H by use of the superimposed template, wherein H is the width of a superimposed range. Therefore, improvements in efficiency can be accomplished, and image

processing can be carried out at a higher speed for face extraction, for example.

【 0 1 3 1 】

(2) Additionally, a rough candidate range of eyes, nose, and mouth can be extracted not only merely by outputting the positional data for a face but also by superimposing the template on the face candidate position as shown in Fig. 14.

【 0 1 3 2 】

The positions of face parts, such the eyes, nose, and mouth, can also be more accurately extracted by processing the images in these ranges much more finely, as described in the following embodiments.

【 0 1 3 3 】

「Second Example」

In this example, a template image processing part 102 is constructed as shown in Fig. 11(b). That is, the position of the addition unit 16 is moved between the compression unit 4 and the recording unit 5, in comparison with the First Example. Thereby, the addition unit 16 is

formed to perform addition processing according to the following formula.

【Formula 15】

wherein the size range is $a \sim b$.

【 0 1 3 4 】

The similarity value formula that is linear before being subjected to Fourier transformation is still linear after being subjected thereto. Therefore, the position of the addition unit 16 can be changed from the First Example to the Second Example, for example.

【 0 1 3 5 】

Thereby, an object to be processed by the addition unit 16 can be reduced more than in the First Example because the object is compressed by compression unit 4. Therefore, suitably, processing speed can be improved.

【 0 1 3 6 】

(Embodiment 4)

Embodiment 4 will be described with reference to Fig. 15 and Fig. 16. This Embodiment discloses an efficient technique for turning the

value of the maximum point of the similarity value map described in embodiments 1 and 2 into a stronger peak value.

【 0 1 3 7 】

Generally, in the similarity value map, a peak appears in a part overlapping with the template image. In this embodiment, a peak pattern "p" around and including a maximum point is used as a filter for the similarity value map, and the value of a part similar to the peak pattern in the similarity value map is amplified.

【 0 1 3 8 】

As shown in Fig. 15, in this embodiment, a peak pattern processing part 300 is added to the structure of Fig. 1 showing embodiment 1.

【 0 1 3 9 】

Fig. 16 shows a mask for this peak pattern. As indicated in Fig. 16, in this peak pattern, normalization is made to set an average value at 0.

【 0 1 4 0 】

In the peak pattern processing part 300, an orthogonal transformation unit 17 subjects this peak pattern to Fourier transformation,

and a compression unit 18 compresses a Fourier transformation value so as to record compressed data in a recording unit 19.

【 0 1 4 1 】

Since the mask is used, the similarity value formula is established not by Formula 8 but by the following formula that reflects the mask.

【Formula 16】

Peak pattern low frequency spectrum

$L(u,v)$: Similarity value before filtering

$M(u,v)$: Similarity value after filtering

【 0 1 4 2 】

Therefore, the multiplication unit 10 reads data from the recording unit 5, the recording unit 19, and the compression unit 9, then performs a product-sum-calculation, and outputs the Fourier transformation value of the similarity value corrected by the peak pattern.

【 0 1 4 3 】

A peak pattern filter can filter the similarity value map L according to the following formula, but, if so, a large amount of product sum

calculations will be inefficiently needed.

【Formula 17】

【 0 1 4 4 】

In contrast, in this embodiment, simple, accurate processing is performed according to Formula 16 without performing a large amount of calculations like Formula 17.

【 0 1 4 5 】

Therefore, according to this embodiment, the peak point of the similarity value map can be efficiently amplified. Additionally, a part similar to the template can be clearly and stably detected from the input image while reflecting the peak pattern.

【 0 1 4 6 】

(Embodiment 5)

In this embodiment, a pixel mean in the range of the template image as well as the similarity value between the edge of the input image and the edge of the template image is added to a similarity judgment.

【 0 1 4 7 】

This structure is shown in Fig. 17. Like Fig. 15, a mask pattern processing part 400 is added to the structure of Fig. 1 of Embodiment 1.

【 0 1 4 8 】

However, the structure of Fig. 17 differs from that of Fig. 15 in the fact that the mask pattern processing part 400 is used not to input a peak pattern but to input a template image, and that a mask pattern generation unit 20 is provided for generating a mask pattern that depends on this image.

【 0 1 4 9 】

Like Fig. 15, the output of the mask pattern generation unit 20 is subjected to Fourier transformation by the orthogonal transformation unit 21, is then compressed by the compression unit 22, and is recorded in the recording unit 23.

【 0 1 5 0 】

Further, since a mask is used, the similarity value formula is expressed not as Formula 8 but as the following formula that reflects the mask.

【Formula 18】

$Q(x,y)$: Pixel-average-added similarity value

$q(l,m)$: Mask pattern

$L(x,y)$: Similarity value before filtering

$I(x,y)$: Input image data

【 0 1 5 1 】

For the same reason mentioned in Embodiment 4, a large amount of product sum calculations will be inefficiently needed if multiplication is performed in this way.

【 0 1 5 2 】

Formula 19 is obtained by subjecting this to Fourier transformation, and the calculation can be performed very simply.

【Formula 19】

【 0 1 5 3 】

Therefore, the multiplication unit 10 performs a product-sum-calculation according to Formula 19.

【 0 1 5 4 】

Next, the relationship between the template image and the mask pattern will be described with reference to Fig. 18. Herein, in order to add a pixel mean in the range of the template image to a similarity judgment, the mask pattern generation unit 20 generates a mask pattern as shown in Fig. 18(b) for a template image as shown in Fig. 18(a)

【 0 1 5 5 】

In greater detail, in the template image of Fig. 18(a), a value of $1/N$ is set at each point of the inner part (inside the circle) whose pixel mean is to be calculated, and a value of 0 is set at other points. Herein, N is the number of points in the inner part, and a result of an addition of the value of all points of the mask pattern is 1.

【 0 1 5 6 】

According to this embodiment, a mean of pixel values inside the image can also be added to the similarity value, and a specified object can be extracted from the input image more accurately and more efficiently.

【 0 1 5 7 】

A mean of a square value of each pixel can be calculated such that data in which each pixel of the input image is squared by the input image processing part is formed, and the same processing is applied thereto.

【 0 1 5 8 】

Therefore, a distributed value as well as a mean within a range can be efficiently calculated.

【 0 1 5 9 】

(Embodiment 6)

This embodiment discloses a technique by which a bilaterally symmetric image with respect to a template image can be efficiently processed.

【 0 1 6 0 】

This structure is shown in Fig. 19. That is, in addition to the structure of Fig. 1 of Embodiment 1, a symmetric vector generation unit 24 is provided between the recording unit 5 and the multiplication unit 10. As in Embodiment 1, Formula 8 is used as the similarity value formula in this embodiment.

【 0 1 6 1 】

Next, a description will be given of how to treat a bilaterally symmetric template image. For example, if the template image of Fig. 20(a) is an original image, a template image in which the original one has been bilaterally reversed is shown as in Fig. 20(b).

【 0 1 6 2 】

The relationship between the edge normal direction vectors of these template images is expressed by the following formula.

【Formula 20】

: Edge normal direction vector of image resulting from subjecting original template image to bilateral reversal

【 0 1 6 3 】

The evaluation vector of the template image that has been bilaterally reversed is expressed by the following formula.

【Formula 21】

Evaluation vector of

Evaluation vector of

【 0 1 6 4 】

Concerning Fourier transformation, because of the relation of Formula 22, Formula 23 is obtained by applying Formula 22 to Formula 21.

【Formula 22 】

【Formula 23 】

【 0 1 6 5 】

In detail, the evaluation vector of the template image that has been bilaterally reversed can be easily generated by, for example, reversing the positive and negative of the evaluation vector of the original template image.

【 0 1 6 6 】

Therefore, the evaluation vector of the template image that has been bilaterally reversed can be obtained only by allowing the symmetric vector generation unit 24 to apply Formula 23 to the evaluation vector of the original template image of the recording unit 5 in Fig. 19.

【 0 1 6 7 】

When simply assumed, there is no need to perform complex processing, such as a procedure in which the image of Fig. 20(b) is generated from the image of Fig. 20(a), and the evaluation vector is again calculated from the image of Fig. 20(b).

【 0 1 6 8 】

Thereby, the evaluation vector of the template image that has been bilaterally reversed can be generated without direct calculations, and processing speed can be improved. Additionally, recording capacity can be saved because the need to purposely store the template image that has been bilaterally reversed is obviated.

【 0 1 6 9 】

(Embodiment 7)

In this embodiment, eye/eyebrow extraction processing is added to the face extraction processing described in Embodiment 3.

【 0 1 7 0 】

As in Fig. 22(b), eyes/eyebrow candidate range can be roughly

extracted from the input image of Fig. 22(a) according to the processing described in Embodiment 3.

【 0 1 7 1 】

Point biserial correlation coefficient filters shown in Fig. 23(a) through Fig.23(d) are applied onto each point of the image of this eye/eyebrow candidate range, a map of point biserial correlation values is then formed, and points where the correlation value in the map become high are set as the eyes center point 3002 and as an eyebrow center point 3003, respectively.

【 0 1 7 2 】

The point biserial correlation coefficient η is defined by the following formula (reference; Multivariate Analysis Handbook, page 17, Modern Mathematics).

【Formula 24】

Overall range: addition of 1st range to 2nd range

Number of pixels of 1st range

n: Number of pixels of overall range

Average brightness level of 1st range

Average brightness level of 2nd range

S: Standard deviation of overall range

Value in $\sqrt{\quad}$ is constant when mask size is fixed.

【 0 1 7 3 】

Referring to Fig. 23(a) through Fig.23(d), Fig. 23(a) shows the positional relationship of all ranges, Fig. 23(b) shows an overall range mask, Fig. 23(c) shows a 1st range mask, and Fig. 23(d) shows a 2nd range mask.

【 0 1 7 4 】

If the filter shape according to this point biserial correlation coefficient is formed as shown in Fig. 23(a), it will be expected that the eyebrow center 3002 and the eye center 3003 can be extracted as shown in Fig. 22(c).

【 0 1 7 5 】

Next, filter processing according to the point biserial correlation coefficient will be described.

【 0 1 7 6 】

First, main components of Formula 24 are expressed by the following formula.

【Formula 25】

wherein,

M1: 1st range mask

M2: 2nd range mask

Ma: Overall range mask

I(x,y): Each pixel value of input image

【 0 1 7 7 】

The following formulas are obtained by subjecting each component to Fourier transformation.

【Formula 26】

【Formula 27】

【Formula 28】

wherein

【 0 1 7 8 】

In order to perform these processings, the structure of Fig. 21 is formed, for example. First, each mask of the overall range, the 1st range, and the 2nd range is subjected to Fourier transformation by the orthogonal transformation unit 51 through 53.

【 0 1 7 9 】

An input image and a result of the face extraction described in Embodiment 3 are input to the eye/eyebrow candidate range extraction unit 54 through the map processing unit 12. Based on these inputs, the eye/eyebrow candidate range extraction unit 54 extracts only the eye/eyebrow candidate range shown in Fig. 22(b) from Fig. 22(a). Data concerning this eye/eyebrow candidate range is subjected to Fourier transformation by an orthogonal transformation unit 55 without any changes, is then squared by a square unit 56, and is subjected to Fourier transformation by an orthogonal transformation unit 57.

【 0 1 8 0 】

Thereafter, data shown in Formula 27 is input through a

multiplication unit 58 to an inverse orthogonal transformation unit 62 precedent to a η map forming unit 65. Likewise, data shown in Formula 26 is input to an inverse orthogonal transformation unit 63 through a multiplication unit 60, and data shown in Formula 28 is input to an inverse orthogonal transformation unit 64 through a multiplication unit 61. The input data is subjected to inverse Fourier transformation by the inverse orthogonal transformation unit 62 through 64, and is output to the η map forming unit 65.

【 0 1 8 1 】

Thereafter, the η map forming unit 65 performs a calculation according to Formula 24 when receiving the data from the inverse orthogonal transformation unit 62 through 64, and outputs a map $\eta(x,y)$ of the point biserial correlation coefficient.

【 0 1 8 2 】

The eye/eyebrow center extraction unit 66 extracts two points having high values from the map $\eta(x,y)$ output by the η map forming unit 65, and outputs them as the eyes center and an eyebrow center,

respectively.

【 0 1 8 3 】

In this structure, multiplication must be performed roughly $15 \times 15 \times N = 225N$ times, wherein " 15×15 " (pixels) is the filter size of Fig. 23(a), and N is the number of pixels of the input image.

【 0 1 8 4 】

In contrast, according to this embodiment, the number of product calculations is roughly $N + [(2^{\gamma} - 4)N + 4] \times 5 + 12N + N + N = 5N(2^{\gamma} - 1) + 20$ times. For convenience, the calculation of " $\sqrt{\quad}$ " is assumed as equal to one multiplication processing.

【 0 1 8 5 】

That is, (calculation amount of this embodiment) < (calculation amount of the conventional technique) under the condition that γ is 22 or less.

【 0 1 8 6 】

Usually, a huge image in which N is 2^{22} or more is not used.

Therefore, it is understood that the image processing of this embodiment is smaller in the number of calculation times than that of the conventional processing, and is performed faster than that of the conventional processing.

【 0 1 8 7 】

Thus, according to this embodiment, the point biserial correlation coefficient filter processing can be more efficiently performed.

【 0 1 8 8 】

The positions of other face parts, such as eye corners, mouth edges, nostrils, and irises, can be calculated by variously changing the masks shown in Fig. 23.

【 0 1 8 9 】

(Embodiment 8)

This embodiment discloses a technique for expanding the function of the face extraction according to Embodiment 3 and extracting a mouth range, which is a facial organ, from a face image.

【 0 1 9 0 】

As described in Embodiment 3 with reference to Fig. 14, a mouth candidate range shown in Fig. 25(b) can be extracted from the input image of Fig. 25(a).

【 0 1 9 1 】

When the extracted mouth candidate range is projected onto the Y-axis (i.e., when the total h of pixel values is plotted along the X-axis), a graph roughly shown in Fig. 25(c) is obtained.

【 0 1 9 2 】

The total h is defined by the following formula.

【Formula 29】

$I(x,y)$: Each pixel value of input image

w : Width of mouth candidate range

$h(x,y)$: Projection value

【 0 1 9 3 】

In order to efficiently obtain this total by use of orthogonal transformation, a mask shown in Fig. 25(d) is prepared. Formula 29 can be rewritten like the following formula, including this mask.

【Formula 30】

Mask

【 0 1 9 4 】

When this is subjected to Fourier transformation, the following formula is obtained.

【Formula 31】

【 0 1 9 5 】

That is, what is required to obtain this projection value is to subject the input image and the mask pattern to Fourier transformation, thereafter perform the calculation of Formula 31, and subject its result to inverse Fourier transformation. Thereby, the map "h(x,y)" of the projection value "h" can be obtained.

【 0 1 9 6 】

From the above result, it is desirable to form the structure of Fig. 24, for example. As shown in Fig. 24, the input image and the mask pattern are subjected to Fourier transformation by the orthogonal transformation unit 25 and 26, respectively.

【 0 1 9 7 】

Thereafter, the transformation value is multiplied by the multiplication unit 27, and is subjected to inverse Fourier transformation by the inverse orthogonal transformation unit 28. As a result, the map $h(x,y)$ of the projection value is obtained.

【 0 1 9 8 】

The obtained map $h(x,y)$ is developed by a projection data extraction unit 29, and a maximum point extraction unit 30 calculates two maximum points from this map, and outputs the range between these maximum points as mouth range.

【 0 1 9 9 】

The mask pattern can be, of course, beforehand subjected to Fourier transformation as in Embodiment 1, and, if so, a processing performance can be concentrated on the processing of the input image, and processing speed will be improved.

【 0 2 0 0 】

According to this embodiment, the position of the mouth, which is

a facial organ, (more specifically, the positions of both the upper and lower lips) can be accurately calculated.

【 0 2 0 1 】

(Embodiment 9)

This embodiment discloses a technique for expanding the function of the face extraction according to Embodiment 3, and applying predetermined processing to a face image according to first and second examples of this embodiment.

【 0 2 0 2 】

「First Example」

In this example, a digital watermark is embedded into an extracted face image. That is, the structure of Fig. 26 is formed. A result using part 600 is provided at the subsequent stage of the map processing unit 12 of Fig. 11.

【 0 2 0 3 】

The result-using part 600 includes a face image cutting-out unit 31 for separating an input image into a face image and a non-face image with

reference to the input image and the face position that is determined by the map processing unit 12. The face image part is output from the face image cutting-out unit 31 to a digital watermark embedding unit 32, and a predetermined digital watermark is embedded into the face image part. Herein, this digital watermark can be a well-known one.

【 0 2 0 4 】

On the other hand, the part excluding the face image is output from the face image cutting-out unit 31 directly to an image synthesizing unit 33.

【 0 2 0 5 】

The image synthesizing unit 33 combines the face image into which the digital watermark is embedded with the part excluding the face image, and outputs an image into which the digital watermark has been embedded.

【 0 2 0 6 】

Therefore, with respect to, for example, an input image of Fig. 27(a), an output image of Fig. 27(b) into a face part of which a digital

watermark has been embedded is obtained.

【 0 2 0 7 】

The name of a model to be photographed or the date of the photograph is suitable as a digital watermark.

【 0 2 0 8 】

According to this example, watermark data can be concentratively and easily embedded into a face part that is liable to be falsified.

【 0 2 0 9 】

「Second Example」

In this example, specific editing is applied only to an extracted face image. That is, the structure of Fig. 28 is formed. A result-using part 601 is provided at the subsequent stage of the map processing unit 12 of Fig. 11.

【 0 2 1 0 】

The result-using part 601 includes the face image cutting-out unit 31 for separating an input image into a face image and a non-face image with reference to the input image and the face position that is determined

by the map processing unit 12. The face image part is output from the face image cutting-out unit 31 to an image correction unit 34, and predetermined editing is applied to the face image part. Herein, the editing can be a well-known one.

【 0 2 1 1 】

On the other hand, the part excluding the face image is output from the face image cutting-out unit 31 directly to the image synthesizing unit 33.

【 0 2 1 2 】

The image synthesizing unit 33 combines the face image that has been edited with the part excluding the face image, and outputs an edited image.

【 0 2 1 3 】

Therefore, referring to, for example, an input image of Fig. 29(a), an output image in which a face range has been extracted like Fig. 29(b), and only a face part has been edited like Fig. 29(c) is obtained.

【 0 2 1 4 】

In an image of a person photographed by counter light, an image of the face part might be corrected so that a face color becomes whitish, because the face is too dark and is hard to see. However, in the editing by the image correction unit 34, such an image may be arbitrarily corrected.

【 0 2 1 5 】

According to this example, an image of only the face part can be easily and selectively corrected, or, in other words, image correction can be performed without exerting an influence on a part excluding the face.

【 0 2 1 6 】

「Third Example」

In this example, an extracted face image is corrected to be easily perceptible. That is, the structure of Fig. 30 is formed. First, a result-using part 602 is provided behind the map processing unit 12 of Fig. 11.

【 0 2 1 7 】

The result-using part 602 includes the face image cutting-out unit

31 for separating an input image into a face image and a non-face image. A face image that has been cut out is output to a face internal range extraction unit 35 and to the image correction unit 34.

【 0 2 1 8 】

According to the procedure described in Embodiment 3, the face internal range extraction unit 35 calculates the positions of main face parts, such as eyes, nose, and mouth, from the cut-out face image by use of a template, and extracts a facial inner image (i.e., image that is situated inside the whole face). In this example, the facial inner image is an image in a rectangular range having a predetermined size and centering the face center (e.g., the center of the nose). However, the size of the rectangular range can be changed, and the center can be located at a position slightly deviated from the face center.

【 0 2 1 9 】

The extracted facial inner image is output to an image feature extraction unit 36. The image feature extraction unit 36 calculates a useful feature for correction of a face image. In this example, the image

feature extraction unit 36 calculates brightness distribution of a facial inner image, and outputs its result to a correction function determining unit 37 in the form of a brightness histogram. The image feature extraction unit 36 can, of course, output a brightness minimum value and a brightness maximum value in the brightness histogram to the correction function determining unit 37.

【 0 2 2 0 】

The correction function determining unit 37 determines a correction function by which the contrast of the facial inner image becomes clearer with reference to a feature input from the image feature extraction unit 36, and outputs this correction function to the image correction unit 34.

【 0 2 2 1 】

In this example, the image feature extraction unit 36 outputs the brightness histogram as mentioned above, and therefore the correction function determining unit 37 calculates a correction function so that the minimum brightness that appears in the histogram reaches the minimum

brightness in the dynamic range, and so that the maximum brightness reaches the maximum brightness therein. Thereafter, the correction function determining unit 37 outputs the correction function to the image correction unit 34.

【 0 2 2 2 】

The horizontal axis of the brightness histogram of Fig. 30 indicates brightness values, and it will be understood that only a part of the dynamic range that can express brightness is used. Therefore, the correction function determining unit 37 determines the correction function so as to fully use the dynamic range, and thereby the image correction unit 34 can correct the face image so that the image can be easily discerned, or, more specifically, so that it can have abundant gradations in appearance. As a result of this correction, the face image infallibly easily viewable though there might be a situation in which a part other than the face image is whitened or darkened.

【 0 2 2 3 】

Herein, since the correction function is determined on the basis of

only the facial inner image, correction is never misled by a non-face part. Therefore, after correction, it can be guaranteed that viewability of the face is improved.

【 0 2 2 4 】

Although Fig. 30 shows the drawing so as if to make correction only to the cut-out face image, similar correction can be made to the whole input image.

【 0 2 2 5 】

Further, as a feature to be sought by the image feature extraction unit 36, an index that represents the lightness/darkness of an image, such as brightness, can be used as described above. In addition, a chroma average or a hue average can be used.

【 0 2 2 6 】

If the chroma average is used, the correction function determining unit 37 can output, for example, a chroma amplification coefficient to the image correction unit 34, and, if the hue average is used, the correction function determining unit 37 can output, for example, a hue rotational

angle to the image correction unit 34.

【 0 2 2 7 】

Herein, a pale face image can be more vividly corrected when the chroma average is used as a feature, and, when the hue average is used, a less reddish face image can be corrected to be more reddish. In either case, the face image can be made more natural. Additionally, a combination of two or more of brightness, chroma average, or hue average can be used as a feature.

【 0 2 2 8 】

[EFFECT OF THE INVENTION]

According to the present invention, patterns can be extracted stably and at high speed with less influence of the difference of the photographic condition and background.

【 0 2 2 9 】

Patterns of a plurality of templates can also be extracted at high speed.

【 0 2 3 0 】

The similarity value map can be amplified and a part similar to the template can be stably detected from the input image.

【 0 2 3 1 】

Attributes inside the image can be added to the similarity value, and can be processed more clearly and more efficiently.

【 0 2 3 2 】

Data of the template image that have been bilaterally reversed can be generated indirectly, and data amount of the template image can be reduced.

【 0 2 3 3 】

An object to be processed can be reduced rationally.

【 0 2 3 4 】

Point biserial correlation coefficient filters can extract the center point of eyes and eyebrows.

【 0 2 3 5 】

A mouth range, which is a facial organ can be specified accurately.

【 0 2 3 6 】

Watermark data can be concentratively embedded into a face part that is liable to the falsified.

【 0 2 3 7 】

An image only the face part can be selectively performed the image correction.

【 0 2 3 8 】

According to the feature of only the facial inner image, the viewability of the face image can be infallibly improved.

[DESCRIPTION OF DRAWINGS]

[Fig. 1]

Fig. 1 is a block diagram of an image processing apparatus according to Embodiment 1 of the present invention.

[Fig. 2]

Fig. 2 (a) is a view showing a template image.

Fig. 2 (b) is a view showing an edge extraction image (x component) of the template image.

Fig. 2 (c) is a view showing an edge extraction image (y component) of the template image.

[Fig. 3]

Fig. 3 is an explanatory drawing for explaining the compression processing of an evaluation vector.

[Fig. 4]

Fig. 4 (a) is a view showing an input image.

Fig. 4 (b) is a view showing an edge extraction image (x component) of the input image.

Fig. 4 (c) is a view showing an edge extraction image (y component) of the input image.

[Fig. 5]

Fig. 5 (a) is a view showing a map of similarity values.

Fig. 5 (b) is a view showing the input image.

[Fig. 6]

Fig. 6 is an explanatory drawing for explaining a positive/negative reversal of an inner product.

[Fig. 7]

Fig. 7 (a) is a view showing a template image.

Fig. 7 (b) is a view showing an input image.

[Fig. 8]

Figs. 8 (a) is a view showing a template image.

Figs. 8 (b) is a view showing a template image.

[Fig. 9]

Fig. 9 is a block diagram of an image processing apparatus according to Embodiment 2 of the present invention.

[Fig. 10]

Figs. 10 (a) is a graph showing conjugate properties.

Figs. 10 (b) is a graph showing conjugate properties.

[Fig. 11]

Fig. 11 (a) is a block diagram of a template image processing part according to Embodiment 3 (first example) of the present invention.

Fig. 11 (b) is a block diagram of a template image processing part according to Embodiment 3 (second example) of the present invention.

[Fig. 12]

Fig. 12 is a view showing an input image.

[Fig. 13]

Fig. 13 (a) is a view showing a template image.

Fig. 13 (b) is a view showing an edge extraction image.

Fig. 13 (c) is a view showing an enlargement/reduction template image.

Fig. 13 (d) is a view showing a template image.

Fig. 13 (e) is a view showing an edge extraction image.

Fig. 13 (f) is a view showing an enlargement/reduction template image.

[Fig. 14]

Fig. 14 is a view showing a face extraction result.

[Fig. 15]

Fig. 15 is a block diagram of an image processing apparatus according to Embodiment 4 of the present invention.

[Fig. 16]

Fig. 16 is a view showing a peak pattern.

[Fig. 17]

Fig. 17 is a block diagram of an image processing apparatus according to Embodiment 5 of the present invention.

[Fig. 18]

Fig. 18 (a) is a view showing a template image.

Fig. 18 (b) is a view showing a mask pattern.

[Fig. 19]

Fig. 19 is a block diagram of an image processing apparatus according to Embodiment 6 of the present invention.

[Fig. 20]

Fig. 20 (a) is a view showing an original template image.

Fig. 20 (b) is a view showing a template image that has been subjected to a bilateral reversal.

[Fig. 21]

Fig. 21 is a block diagram of a part of the image processing apparatus according to Embodiment 6 of the present invention.

[Fig. 22]

Fig. 22 (a) is a view showing an input image.

Fig. 22 (b) is a view showing the eyes/eyebrow candidate range.

Fig. 22 (c) is a view showing a recognition result.

[Fig. 23]

Fig. 23 (a) is a view showing a filter shape according to Embodiment 7 of the present invention.

Fig. 23 (b) is an explanatory drawing of an overall range mask.

Fig. 23 (c) is an explanatory drawing of a range-1 mask.

Fig. 23 (d) is an explanatory drawing of a range-2 mask.

[Fig. 24]

Fig. 24 is a block diagram of a part of an image processing apparatus according to Embodiment 8 of the present invention.

[Fig. 25]

Fig. 25 (a) is a view showing an input image.

Fig. 25 (b) is an explanatory drawing of a mouth candidate range.

Fig. 25 (c) is a graph of projection values.

Fig. 25 (d) is an explanatory drawing of a mask pattern.

Fig. 25 (e) is a view showing a projection-value map image.

Fig. 25 (f) is a graph of projection values.

[Fig. 26]

Fig. 26 is a block diagram of a part of an image processing apparatus according to Embodiment 9 (first example) of the present invention.

[Fig. 27]

Fig. 27 (a) is a view showing an input image.

Fig. 27 (b) is a view showing an output image.

[Fig. 28]

Fig. 28 is a block diagram of a part of the image processing apparatus according to Embodiment 9 (second example) of the present invention.

[Fig. 29]

Figs. 29 (a) is a view showing an input image.

Figs. 29 (b) is a view showing an output image.

[Fig. 30]

Fig. 30 is a block diagram of a part of the image processing apparatus according to Embodiment 9 (third example) of the present invention.

[DESCRIPTION OF SYMBOLS]

- 1 edge extraction unit
- 2 evaluation vector generation unit
- 3 orthogonal transformation unit
- 4 compression unit
- 5 recording unit
- 6 edge extraction unit
- 7 evaluation vector generation unit
- 8 orthogonal transformation unit
- 9 compression unit
- 10 multiplication unit
- 11 inverse orthogonal transformation unit
- 12 map processing unit

- 13 conjugate compression unit
- 14 conjugate reconstruction unit
- 15 enlargement/reduction unit
- 16 addition unit
- 17 orthogonal transformation unit
- 18 compression unit
- 19 recording unit
- 20 mask pattern generation unit
- 21 orthogonal transformation unit
- 22 compression unit
- 23 recording unit
- 24 symmetric vector generation unit
- 25,26 orthogonal transformation unit
- 27 multiplication unit
- 28 inverse orthogonal transformation unit
- 29 projection data extraction unit
- 30 maximum point extraction unit

- 31 face image cutting-out unit
- 32 digital watermark embedding unit
- 33 image synthesizing unit
- 601 result-using part
- 34 image correction unit
- 51 orthogonal transformation unit
- 52 orthogonal transformation unit
- 53 orthogonal transformation unit
- 54 eye/eyebrow candidate range extraction unit
- 55 orthogonal transformation unit
- 56 square unit
- 57 orthogonal transformation unit
- 58 multiplication unit
- 59 reduction unit
- 60 multiplication unit
- 61 multiplication unit
- 62,63,64 inverse orthogonal transformation unit

- 65 η map forming unit
- 66 eye/eyebrow center extraction unit
- 100 template image processing part
- 101,102 template image processing part
- 200 input image processing part
- 300 peak pattern processing part
- 400 mask pattern processing part
- 500 projection image processing part
- 600 result-using part

[DOCUMENT NAME] ABSTRACT

[ABSTRACT]

[PROBLEM TO BE SOLVED] It is an object of the present invention to provide an image processing method and an image processing apparatus capable of obtaining an accurate, clear recognition result and capable of performing high speed processing.

[SOLUTION] An image processing method for detecting an object from an input image by use of a template image. The image processing method includes a step of inputting a specified image with respect to both a template image and an input image, a step of calculating an edge normal direction vector of the specified image, a step of generating an evaluation vector from the edge normal direction vector, a step of subjecting the evaluation vector to orthogonal transformation, a step of performing a product sum calculation of corresponding spectral data with respect to each evaluation vector that has been subjected to orthogonal transformation and has been obtained for each of the template image and the input image, and a step of subjecting it to inverse orthogonal

transformation and generating a similarity value map. The formula of the similarity value, the orthogonal transformation, and the inverse orthogonal transformation each have linearity. It is possible to make pattern recognition in which the component of the similarity value is not subjected to positive/negative reversal through variations in brightness of its background.

[SELECTED FIGURE] Fig. 1

Fig.1

template image → 1 edge extraction

2,7 evaluation vector generation

4,9 compression

5 recording

input image → 6 edge extraction

11 inverse FFT

12 map processing → result

Fig.2(a)

template image

Fig.2(b)

X component

Fig.2(c)

Y component

Fig.3

object to be processed

Fig.4(a)

input image

Fig.4(b)

X component

Fig.4(c)

Y component

Fig.5(a)

maximum value

Fig.7(a)(b)

background



specified object

template image input image

Fig.9

template image → 1 edge extraction

2,7 evaluation vector generation

4,9 compression

5 recording

input image → 6 edge extraction

11 inverse FFT

12 map processing → result

13 conjugate compression

14 conjugate restoring

Fig.11(a)

1 edge extraction

2 evaluation vector generation

4 compression

5 recording

template image → 15 enlargement/reduction

Fig.11(b)

1 edge extraction

2 evaluation vector generation

4 compression

5 recording

template image→15 enlargement/reduction

Fig.15

template image→1 edge extraction

2,7 evaluation vector generation

4,9,18 compression

5,19 recording

input image→6 edge extraction

11 inverse FFT

12 map processing→result

peak pattern P→17 FFT

Fig.17

template image→1 edge extraction

2,7 evaluation vector generation

4,9,22 compression

5,23 recording

input image→6 edge extraction

- 11 inverse FFT
- 12 map processing→result
- 20 mask pattern generation

Fig.18(a)

template image

Fig.18(b)

mask pattern q

value 0 part

value 1/N part

Fig.19

template image→1 edge extraction

2,7 evaluation vector generation

4,9 compression

5 recording

input image→6 edge extraction

11 inverse FFT

12 map processing→result

24 symmetric vector generation

Fig.21

overall range mask(Ma)

1st range mask(M1)

2nd range mask(M2)

12 map processing

input image→54 eye/eyebrow candidate range extraction

56 square

62,63,64 inverse FFT

65 η map forming

66 eye/eyebrow center extraction→center position

Fig.23(a)

don't care

1st range

2nd range

1st range

Fig.23(b)

overall mask(Ma)

Fig.23(c)

1st range mask(M1)

Fig.23(d)

2nd range mask(M2)

Fig.24

input image→25 FFT

mask pattern →26 FFT

28 inverse FFT

29 projection data extraction

30 maximum point extraction→mouth range output

Fig.25(c)

maximum point

mouth range

projection value

Fig.25(d)

value 0

value 1

Fig.25(e)

mouth candidate position

Fig.25(f)

maximum point

mouth range

projection value

Fig.26

12 map processing→result output face position

input image→31 face image cutting-out

face image→32 digital watermark embedding

non-face image→33 image synthesizing

Fig.27(b)

digital watermark embedded part

Fig.28

12 map processing→result output face position

v axis: frequency h axis: brightness value

title: brightness histogram

correction function graph

v axis: output brightness h axis: input brightness

title: correction function